



ARTOS SAT120LS

THERMAL INSULATED SLIDING SYSTEM
ISI YALITIMLI SÜRME SİSTEMİ

SAT 120 LS system for transparent architecture with maximum comfort, maximum design-compatibility. The highly thermally insulated SAT 120 LS system suits to luxury homes and large projects. The system offers an attractive design with lift & slide mechanism options. SAT 120 LS profile system door vent size can be installed up to 3,500 mm high as lift-and-slide door. Door vent carrying capacity is max. 400 kg. The system offers multipoint locking as security. Using the additional barrel lock will improve safety. 120 LS security locks are multipoint locks. The use of additional barrel locking will increase safety. The system is suitable for automatic lift and slide accessory use.

Maksimum konfor ve maksimum tasarım uyumluluğu ile şeffaf mimari için SAT 120 LS sistemi. Yüksek ısı yalıtımlı SAT 120 LS sistemi lüks evler ve büyük projeler için uygundur. Sistem kaldır sür mekanizma seçenekleri ile çekici bir tasarım sunar. SAT 120 LS profil sistemi kapı kanadı 3.500 mm yüksekliğe kadar, kaldır -sür kapı olarak monte edilebilir. Kanat taşıma kapasitesi max. 400 kg'dır. Sistem güvenlik olarak çok noktalı kilitleme sunar. İlave barel kilitlemesinin kullanılması güvenliği artıracaktır. Sistem, otomatik kaldır sür aksesuarı kullanımı için uygundur.



ARTOS SAT120LS

THERMAL INSULATED SLIDING SYSTEM
ISI YALITIMLI SÜRME SİSTEMİ



Frame Profile External Height	
Single-Rail Frame (mm)	50.5 mm
Double-Rail Frame (mm)	46.5 mm
Three-Rail Frame (mm)	46.5 mm
Clamping Profile External View	
Clamping Front View	99.5 mm
Dimension Limits	
Maximum Vent Weight	250 kg
Maximum Vent Height (H)	300 cm
Maximum Vent Width (W)	200 cm
Glazing Range (With single and double glass options)	
Minimum Glass Thickness	4 mm
Maximum Glass Thickness	36 mm
Profile Wall Thickness	
Maximum Profile Wall Thickness	2 mm
Glazing Method	
EPDM Gasket	✓

