



HEKLA WAT55

INSULATED DOOR & WINDOW SYSTEM
YALITIMLI KAPI & PENCERE SİSTEMİ

Hekla WAT55 with 16 mm heat barrier is designed for door and window applications that require thermal insulation with alternative profile options. It offers functional solutions for a wide variety of applications with different moulds, fittings and equipment combinations. WAT55 works in harmony with sliding systems such as Artos SLAT 64 and SAT 120, and facade system like Bromo CWA50. It is produced in accordance with the Eurogrove channel structure. Ideal for durable, maintenance-free windows and doors. It can be used in a wide variety of applications with all opening accessories and allows the application of PVC accessories as well.

16 mm ısı bariyerine sahip Hekla WAT55, alternatif profil seçenekleri ile ısı yalıtımı gerektiren kapı ve pencere uygulamaları için tasarlanmıştır. Farklı kalıplar, bağlantı parçaları ve donanım kombinasyonları ile çok çeşitli uygulamalar için fonksiyonel çözümler sunar. Hekla WAT55, Bromo CWA50 cephe sistemi ve Artos SLAT 64 ve SAT 120 gibi sürme sistemleri ile uyumlu çalışır. Eurogrove kanal yapısına uygun olarak üretilmiştir. Dayanıklı, bakım gerektirmeyen pencere ve kapılar için idealdir. Tüm açma aksesuarları ile çok çeşitli uygulamalarda kullanılabilir ve PVC aksesuarların da uygulanmasına olanak sağlar.



HEKLA WAT55

INSULATED DOOR & WINDOW SYSTEM
YALITIMLI KAPI & PENCERE SİSTEMİ



Frame Profile External Height	
Frame Profile External Height	55 mm
Vent Profile External Width	
Vent Profile Minimum Width	37 mm
Vent Profile Maximum Width	67 mm
Glazing Range (With single and double glass options)	
Minimum Glass Thickness	4 mm
Maximum Glass Thickness	38 mm
Profile Wall Thickness	
Minimum Profile Wall Thickness	1.6 mm
Maximum Profile Wall Thickness	2 mm
Glazing Method	EPDM Gasket ✓

