



HEKLA WAT63

INSULATED DOOR & WINDOW SYSTEM
YALITIMLI KAPI & PENCERE SİSTEMİ

Hekla WAT 63, with its 24 mm heat barrier, is preferred in the production of exterior architectural building elements that require thermal insulation and sealing with its superior performance. Sealing is achieved using special wicks made of two-component EPDM synthetic rubber. Allowing the use of 8 mm - 42 mm thick glass, WAT63 is compatible with all Amanos systems and allows the application of PVC accessories. It is designed according to the Eurogrove channel structure and can be used in a wide variety of applications with all opening accessories.

24 mm ısı bariyerine sahip Hekla WAT63 üstün performansı ile ısı yalıtımı ve sızdırmazlık gerektiren dış mimari yapı elemanları üretiminde tercih sebebidir. Sızdırmazlık, iki bileşenli EPDM sentetik kauçuktan yapılmış özel fitiller kullanılarak sağlanır. 8 mm - 42 mm kalınlığında cam kullanımına imkan veren WAT63, tüm Amanos sistemleri ile uyumludur ve PVC aksesuar uygulamasına olanak sağlar. Eurogrove kanal yapısına göre tasarlanmıştır ve tüm açma aksesuarları ile çok çeşitli uygulamalarda kullanılabilir.



HEKLA WAT63

INSULATED DOOR & WINDOW SYSTEM
YALITIMLI KAPI & PENCERE SİSTEMİ



Frame Profile External Height	
Frame Profile External Height	63 mm
Vent Profile External Width	
Vent Profile Minimum Width	37 mm
Vent Profile Maximum Width	67 mm
Glazing Range (With single and double glass options)	
Minimum Glass Thickness	8 mm
Maximum Glass Thickness	42 mm
Profile Wall Thickness	
Minimum Profile Wall Thickness	1.6 mm
Maximum Profile Wall Thickness	2 mm
Glazing Method	
EPDM Gasket	✓

