



BROMO CWA50

CURTAIN WALL SYSTEM
CEPHE SİSTEMİ

CWA50 is a facade system with lidded, semi-lidded (2S), and silicone (4S) application alternatives. It impresses with its sealing feature and high performance in thermal insulation. Moreover, it is fully compatible with AMANOS architectural systems. While improving the living and working environment of the building, CWA50 offers unlimited, modern, economical, and flexible solutions to designers.

CWA50; kapaklı, yarı kapaklı (2S) ve silikon (4S) uygulama alternatiflerine sahip bir cephe sistemidir. Sızdırmazlık özelliği ve ısı yalıtımındaki yüksek performansı ile göz doldurur. Ayrıca, Amanos mimari sistemler ile tamamen uyumludur. CWA 50, binanın yaşam ve çalışma alanlarını iyileştirirken tasarımcılara sınırsız, modern, ekonomik ve esnek çözümler sunar.



BROMO CWA50

CURTAIN WALL SYSTEM
CEPHE SİSTEMİ



Facade Front Width External View	50 mm
Vertical-Horizontal Profile Depth	
Vertical Profile Depths	80-100-120-140-160-180-200 mm
Horizontal Profile Depths	60-85-105-125 mm
Glazing Range (With single and double glass options)	
Minimum Glass Thickness	6 mm
Maximum Glass Thickness	32 mm
Profile Wall Thickness	
Minimum Profile Wall Thickness	1.8 mm
Maximum Profile Wall Thickness	2.2 mm
Glazing Method	
Silicone	✓
EPDM Gasket	✓

