

# PRO 1250

## WRAPPING

## TECHNICAL SPECIFICATIONS

### ESPECIFICACIONES TÉCNICAS

### MACHINE FEATURES / CARACTERÍSTICAS DE LA MÁQUINA

Level Of Automation/ Nivel de Automacion	Full Automatic / Automático
Ring Diameter/Diámetro Interior (mm)	1250
Machine Total Length (mm) / Largo de la Máquina	4000
Total Weight (kg) / Peso Total	920
Max. Rotation Speed (Rpm) / Velocidad (rpm)	80
Power supply voltage/Voltage (V)	400 V 3Ph+N 50/60 Hz
Installed total power (kw) / Potencia total (kw)	2.25kw (1.5kw+0.375kw+0.375kw) 3 Motors
Crown Weight (kg)	24,10kg
Min. Packing / Producto Mínimo (mm)	100x18x550 (With Short Part Bridge)
Working Pressure/ Presion (Bar)	6±1

### CONVEYOR FEATURES (BELT TYPE) / CARACTERÍSTICAS DE TRANSPORTADORA

Conveyor Height / Altura de Transportadora (mm)	800-850
Infeed Conveyor Length (Useful) (mm) / Largo Transportadora Entrada	1800
Outfeed Conveyor Lengths (mm) / Largo Transportadora Salida	1800
Conveyor width (mm) / Anchura transportadora	900
Conveyor Speed (m/min) / Velocidad de Transportadora	10
Max. Load Capacity (kg/m) / Capacidad de Carga	140 kg/m
Electric Motor Power (kw) / Potencia Motor Transportadora	0.375 x 2

### FILM (PE/PVC)

Recommended Film thickness (µm) / Grosor	23, 30, 35
Film width (mm) / Anchura Film	250
Max. External diameter of foil / Diámetro Bobina Exterior (mm)	250
Core diameter of foil (mm) / Diámetro Bobina	76

### COMPONENTS AND BRANDS / MARCAS Y LOS COMPONENTES

**SMART SINGLE PANEL CONTROL / PANTALLA INTELIGENTE	
Drive Motor / Motor de Corona	VOLT Motor 1,5 kw (TR)
Reducer for Motor / Reductores Motor	YILMAZ (TR) / POLAT (TR)
Conveyor / Cinta Transportadora	Motorised Belt Type (Megadyne-Italy)
Conveyor Motor / Motor Transportadora	VOLT Motor 0,375 kw x 2 (TR)
PLC	SCHNEIDER / BEIJER (SWEEDEN)
Drivers	SCHNEIDER (FRANCE)
Smart Touch Panel / Pantalla Tactil	SCHNEIDER / BEIJER (SWEEDEN)
Smart Touch Panel / Pantalla Tactil	7 inch High Resolution 800x480 pixel (16:9)
Smart Touch Panel / Pantalla Tactil	Ethernet, USB, 4 x serial
Emergency Stop/ Boton de Emergencia	SCHNEIDER (FRANCE)
24V Power Supply / Fuente de Poder	OMRON (JAPAN)
SSR RELAY / SSR RELE	SCHNEIDER / CROUZET (FRANCE)
Contactora / Contactador	SCHNEIDER (FRANCE)

