



ARAÇ USB ŞARJ CİHAZI



TEKNİK ÖZELLİKLER	STC-CA-1	STC-CC-1	STC-AA-1	STC-UA-2
ÜRÜN KODU	STC-CA-1	STC-CC-1	STC-AA-1	STC-UA-2
Çıkış 1	USB A-PDO/5V-3A/9V-3A/ 12V-2.25A USB A-C-QC(1)5V-3.6A/ 9V-2.5A/12V-2A	Type-C-PDO/5V-3A/9V-3A/ 12V-2.25A Type-C-QC(1)5V-3.6A/ 9V-2.5A/12V-2A	USB A-QC(1)5V-3.6A/ 9V-2.5A/12V-2A	USB A-5V-2.1A
Çıkış 2	Type-C-PDO/5V-3A/9V-3A/ 12V-2.25A Type-C-QC(1)5V-3.6A/ 9V-2.5A/12V-2A	Type-C-PDO/5V-3A/9V-3A/ 12V-2.25A Type-C-QC(1)5V-3.6A/ 9V-2.5A/12V-2A	USB A-QC(1)5V-3.6A/ 9V-2.5A/12V-2A	USB A-5V-2.1A
Giriş voltaj	12-24V DC/ 27W	12-24V DC/ 27W	12-24V DC/ 27W	12-24V DC/ 21W
Tip	USB Type-C PD+QC3.0 Şarj	Type-C PD+QC3.0 Şarj	USB QC3.0 Şarj	USB Şarj
Renk	Siyah	Siyah	Siyah	Siyah
Ürün malzemesi	ABS+PVC	ABS+PVC	ABS+PVC	ABS+PVC
Çalışma sıcaklığı	-20° ~ +80°	-20° ~ +80°	-20° ~ +80°	-20° ~ +80°
Güvenlik standardı	E-Mark	E-Mark	E-Mark	E-Mark

