



GENERAL SPECIFICATIONS

- Hydraulic height adjustment supported with columns, height adjustment on four sides controller
- 4 sections mattress surface , made of compact material
- Trendelenburg,Reverse Trendelenburg .
- Backrest adjustment assisted by double gas spring
- Knee adjustment assisted by double gas spring.
- Foam mattress with Removable, anti-static and fireproof, waterproof and compatible with the size of the stretcher, 90mm mattress thickness
- Full-length X-Ray Translucent, compact laminate mattress platform
- ClearView Technology in a dual-deck design, offers a similar image quality to an X-ray table the convenience and efficiency of mobile platform
- Oxygen tank holder (12 liters) with Velcro protection on ABS covered Subframe
- Compartment integrated in the ABS base suitable to contain simultaneously objects and O2 cylinder.

- Retractable 304 SS stainless steel Glideaway siderails with locking mechanism
- Retractable and Foldable Pushing bars
- Protective corner bumpers - Shockproof protection on four sides made of soft plastic material (castor type)
- Electrostatic powder (Epoxy) coated main frame
- Anti-static and anti-tracing, 360° Swivel, 200mm Castors with central braking mechanism and steer control. Central brake pedals on four corner.
- 5th Castor for easy maneuvering (Ø 150mm)
- Height adjustable & Foldable IV Pole Stand positionable at four corners, Four integrated IV pole receptacles
- Paper Roll hanger
- Urine bag hanger hooks
- Patient Belts
- Monitor Tray (optional)
- Patient Scale (optional)



Technical Details	
Length :	1950mm
External Length(with tampon):	2150mm
Width :	830mm
Side rails opened(Width)	900mm
Backrest Angle :	90°
TR/RTR Angle :	+16°/-16°
Knee Angle :	40°
Foot End Angle :	30°
Height Range(without mattress)	530 – 870mm
Castors Diameter :	200 mm
Mattress Surface :	800 -1900mm
5 th Castor Diameter :	150mm
Mattress Thickness :	90mm
Safe Working Load Capacity :	317,5 Kg

