



AD-1650

BELLATRIX

DELIVERY / BIRTHING BED



TECHNICAL SPECIFICATIONS

- Delivery/birthing bed with 3 electrical motors
- Foot part can be easily moved under the bed during the birth
- Backrest, height, and +/- Trendelenburg movements by electrical motors
- Hand remote control
- 3 pieces compact laminate lying surfaces
- Easy removable ABS plastic head and foot boards
- 2 pieces ABS plastic siderails
- 2 pieces lying degree indicators
- 4 bumpers in each corner
- 125 mm diameter central lock and directional way castors
- Height adjustable chrome nickel coated IV pole
- Drainage suspender
- 2 pieces holding bars
- 2 pieces knee crutches
- Stainless steel (304) waste bin
- Electrostatic powder coating
- 240 V, 50-60 HZ, 24 V

OPTIONAL SPECIFICATIONS

- Manual CPR
- Battery
- Orthopedic hanger
- X-Ray cassette holder
- Matress: Please ask for the alternatives.
- Color: Please ask for the alternatives.

DIMENSIONS

- Overall dimensions: 108 x 153-198 x 60-80h cm
- Lying surface: 81 x 137-182 cm
- Backrest angle: 70°
- Trendelenburg angle: +/- 15°
- Load capacity: 230 kg



📍 Beylikdüzü Organize Sanayi Sitesi Açelya Caddesi P.K.: 34520 No:39/B1 Beylikdüzü / İstanbul - Türkiye

☎ +90-212-576 00 77

✉ duman@duman.com.tr

📷 / dumantechnologyproducts

📠 +90-212-576 83 24

🌐 duman.com.tr

📘 / dumantech