

TOP GLOVE

TOP QUALITY, TOP EFFICIENCY

THE WORLD'S LARGEST MANUFACTURER OF GLOVES

DOUBLE DONNING STERILE LATEX SURGICAL POWDER FREE GLOVE



Functional Benefits:

- Double assurance to avoid cross-infection between users and patients
- Contrast and bright inner colored glove eases the puncture detection
- Fully anatomical design reduces finger fatigue
- Palm textured enhances slip resistance for extra grip and control
- Polymer coating interior enables incredible smooth donning



DOUBLE DONNING STERILE LATEX SURGICAL POWDER FREE GLOVE

DOUBLE DONNING STERILE LATEX SURGICAL POWDER FREE GLOVE

Quality Standards

- Manufactured under QSR (GMP), ISO 9001:2015 and ISO 13485:2016 Quality Management System
- Conforms to ASTM D3577, EN455 and ISO 10282 standards
- Complies to PPE Regulation (EU) 2016/425 requirements

Glove Sizes

- 5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0
- Size of gloves shall be marked in the check box on the shipping carton with black ink

Product Specifications

- Type** : Latex Surgical Gloves, Powder Free, Polymer Coated
- Material** : Natural High Grade Rubber Latex
- Colour** : Green [Inner] / Natural [Outer]
Green [Inner] / Brown [Outer]
- Design & Features** : Hand specific, curved fingers, palm textured, beaded cuff
- Sterilization** : Yes
- Storage** : The gloves shall maintain their properties when stored in a dry condition. Avoid direct sunlight
- Shelf-life** : The gloves shall have shelf life of 5 years from the date of manufacture
- Application** : Higher Risk or Intensive Surgery



Physical Dimensions

Dimensions	Standards						
	Top Glove				ASTM D3577	EN 455	ISO 10282
Type	LSGPF 7.0g & 7.8g		SDGKF 9.6g & SDBTKF 11.8g		ALL		
Length (mm)	Inner	Outer	Inner	Outer	Min 245 (5.5) Min 265 (6.0 to 9.0)	Min 250 (5.5) Min 260 (6.0 to 6.5) Min 270 (7.0 to 8.0) Min 280 (8.5 to 9.0)	
		Min 280 mm		Min 275 mm		Min 295 mm	
Palm Width (mm)							
• 5.5	72 ± 4				70 ± 6	72 ± 4	72 ± 4
• 6.0	77 ± 5				76 ± 6	77 ± 5	77 ± 5
• 6.5	83 ± 5				83 ± 6	83 ± 5	83 ± 5
• 7.0	89 ± 5				89 ± 6	89 ± 5	89 ± 5
• 7.5	95 ± 5				95 ± 6	95 ± 5	95 ± 5
• 8.0	102 ± 6				102 ± 6	102 ± 6	102 ± 6
• 8.5	108 ± 6				108 ± 6	108 ± 6	108 ± 6
• 9.0	114 ± 6				114 ± 6	114 ± 6	114 ± 6
Thickness : Single Wall (mm)							
• Finger	Min 0.10		0.18 ± 0.02	0.25 ± 0.02	Min. 0.10	N/A	Smooth area [Min: 0.10] Textured area [Min: 0.13]
• Palm			0.17 ± 0.02	0.23 ± 0.02			
• Cuff			0.16 ± 0.02	0.19 ± 0.02			

Physical Properties

Property	ASTM D3577	EN 455	ISO 10282
Tensile Strength (MPa)			
• Before Aging	Min. 24	N/A	N/A
• After Aging	Min. 18	N/A	N/A
Elongation at Break (%)			
• Before Aging	Min. 750	N/A	Min. 700
• After Aging	Min. 560	N/A	Min. 550
Median Force at Break (N)			
• Before Aging	N/A	Min 9	Min 12.5
• After Aging	N/A	Min 9	Min 9.5
Force at 300% Elongation (N)			
• Before Aging	N/A	N/A	Max 2
• After Aging	N/A	N/A	N/A



International Quality Certificate Awarded:



If you have any enquiries on our products, please contact :

TOP GLOVE SALES & CORPORATE OFFICE

Top Glove Tower, 16, Persiaran Setia Dagang, Setia Alam, Seksyen U13, 40170 Shah Alam, Selangor D.E., Malaysia.

+603 3362 3098

+603 3362 5096 (Sales)

sales@topglove.com.my

https://www.facebook.com/topgloveproducts

www.topglove.com