# BRIMSTONE Sulphur provider company

## 1% OIL TREATED SULFUR (45 μm)

**TECHNICAL DATA** 

NUM.VERSION: 1 DATE: 09.01.2023

PRODUCT:	1% OIL TREATED SULFUR (45 microns)
Apearance:	Non flying yellow powder
Baseltem:	Sulfur 99.5% + Oil 1%
Expiration:	2 years
<b>Additional Comments:</b>	

PROPERTY	PRODUCT SPECIFICATION	OBSERVATIONS
Sulfur (%)	99,5+- 2,00	
Oil (%)	1,00+-0,02	
Ash ( % )	<= 0,03	
Moisture (%)	<= 0,5	
Acidity (%)	<= 0,03	
Refusal Sieve 45 µm (325 ASTM) ( % )	<= 5,00	

#### PRODUCT DESCRIPTION:

Micronized sulfur with 1% oil, used in various industrial processes especially in rubber vulcanization.

#### **INSTRUCTIONS AND RECOMMENDATIONS FOR USE:**

#### STORAGE:

Keep the product in a cool, well-ventilated and closed place in its original container for its good conservation. In addition, it is recommended to avoid exposure of the product to extreme temperatures. For safety, keep away from food products and out of reach of children.

### WARNINGS AND PRECAUTIONS DURING HANDLING:

Handle the product in open and well-ventilated spaces. Avoid any physical contact with the product. If it is not possible, clean the affected area with plenty of water.

BRIMSTONE KIMYA SAN. TIC. A.S.

General Manager

EFE MÜNİP NURDOĞDU

