

FN 770FR

Otomatik Kopya Freze Makinesi (3 eksen)
Automatic Copy Router Machine (3 axis)



ALU
PVC
WD

TR Özellikler

– FN 770FR, alüminyum ve plastik profillere 3 yüzeyinde kilit, kol yeri, menteşe, ispanyolet yuvaları ve kanal açma gibi bir çok frezeleme ve delik delme işlemleri için kullanılır.

- Motor hızı ayarlanabilir spindle kopya freze motoru
- Pnömatik mngenelerle sabitlenen malzemenin -90° ve +90° arasında hareket kabiliyeti ile 3 yüzeyinde hassas operasyon imkanı
- -90° ve +90° arasında işlem yapabilmeyi sağlamak amacı ile tablayı sabitleyen güçlü fren mekanizması
- Kolay bıçak değiştirme sistemi
- Operasyonları kolaylaştıran yüksek hassasiyetli gaz amortisörler, yataklama sistemi ve ergonomik kol tasarımı
- Soğutma sistemi
- İşleme uygun kopya tertibatı
- Dayamalar yardımıyla kopya tertibatından bağımsız kanallar açma imkanı
- Sağ ve sol tarafta konveyör, sağ konveyörde cetvel ve dayama sistemi

Standart Ekipmanlar

- 5mm freze ucu (1 adet)
- Sağ ve sol profil dayama
- Soğutma sistemi
- Kopya şablonu
- 4x pnömatik yatay mengene
- Hava tabancası

Opsiyonel Ekipmanlar

- İlave freze ucu
- Özel kopya tertibatı

EN Features

– FN 770FR, used for locks, handles, hinges, espagnolette holes, latch slots, and water drain slot opening processes with rotating the profile on 3 surfaces of aluminum and plastic profiles.


- Adjustable motor speed thanks to spindle copy router motor
- The materials hold by pneumatic clamps mounted on a tilting support can be automatically tilted on any positions, between -90° and +90°
- Equipped with strong table brake system to stop the turning table and machining the profile in any angle between -90° and +90°
- Ease tool changing system
- Smooth movement, high precision and great sensitivity provided with gas spring and ergonomic handles
- Cooling system
- Copy assembly matching the process
- Ability to open various channels independently of the copy assembly with profile gauges
- Roller support table at the right (with ruller) and left side

Standard Equipments


- 5mm milling cutter (1 pcs)
- Right and left profile gauge
- Cooling system
- Copy template equipped with machine
- 4x pneumatic horizontal clamps
- Air gun

Optional Equipments

- Additional milling cutter
- Special copy assembly




HP 3
kW 2.2
n 18.000 r.p.m
V 220-240
Hz 300
A 6.7



x 585 mm
y 300 mm
z 250 mm



6 - 8 BAR



1450x1400x1800mm



300 kg / 350 kg