

# 2137 SOLTON



TEKNİK ÖZELLİKLER	TECHNICAL SPECIFICATIONS
TABLA ÖLÇÜLERİ : 2100 X 3660 Z:300	TABLE DIMENSIONS : 2100 X 3660 Z:300
TABLA MALZEMESİ : KOMPAKT / GENTAŞ	TABLE MATERIAL : COMPACT / GENTAŞ
DİŞLİ VE PİNYON SİSTEMİ : 25X25XMOD2 HELİSEL, SERT, TAŞLANMIŞ / BRL	RACK&PINION SYSTEM : 25X25XMOD2 HEL., HARD., GRINDED / BRL
RAY VE DİŞLİ SİSTEMİ : Y 25 X 25 Z 25 / BRL	GUIDE & BEARING : Y 25 X 25 Z 25 / BRL
KAPLIN : STANDART TİP / GTEN	COUPLING : STANDARD TYPE / GTEN
VİDALI MİL : 25X05 / GTEN	SCREW : 25X05 / GTEN
GÖNYE SİSTEMİ : OTOMATİK / MAG	MITER SYSTEM : AUTOMATIC / MAG
VAKUM BÖLGELERİ : 5 BÖLME – MANUEL / HIMMEL	VACUUM SECTIONS : 5 SECTION – MANUEL / HIMMEL
VAKUM POMPASI : 250 m <sup>3</sup> /Saat KURU TİP – BLOWER - GEV	VACUUM PUMP : 250 m <sup>3</sup> /Hour DRY PUMP - BLOWER - GEV
YAĞLAMA SİSTEMİ : MANUEL 17 NOKTA / KEYLUBE	LUBRICATION SYSTEM : MANUEL 17 POINTS / KEYLUBE
REDÜKTÖRLER : FE100 R:1/10 / LIMING	REDUCERS = FE100 R:1/10 / LIMING
TAKIM DEĞİŞTİRME : OTOMATİK / 10 / TABLA ARKASI / 4 TUTUCU	TOOL CHANGER : AUTOMATIC / 10 / BEHIND TABLE / 4 HOLDER
İŞLEME MOTORU : 9.5 kW 24.000 RPM / AREL	SPINDLE MOTOR : 9.5 kW 24.000 RPM / AREL
CNC KONTROL ÜNİTESİ : DELTA CNC KONTROL	CNC CONTROL UNIT : DELTA CNC CONTROL
SERVO MOTORLAR : 1.0 kW 2000 RPM / DELTA	SERVO MOTORS : 1.0 kW 2000 RPM / DELTA

MAKİNE BİLGİLERİ	MACHINE INFORMATION
KURULUM ÖLÇÜLERİ : W/3000 L/6000 H/2300	INSTALLATION DIMENSIONS : W/3000 L/6000 H/2300
PAKETLEME ÖLÇÜLERİ : W/2200 L/6000 H/2300	PACKAGE DIMENSIONS : W/2200 L/6000 H/2300
ENERJİ TÜKETİMİ : 25 kW	ENERGY CONSUMPTION : 25 kW
HAVA İHTİYACI : 7 Bar	AIR REQUIREMENTS : 7 Bar
AĞIRLIK : 3000 Kg	WEIGHT : 3000 Kg