



Transporter

Weight capacity: 120 kg
 Working Radius: 3000 mm
 Vertical Lift: 1800 mm
 Air consumption: 50 nl/min



Supporter

Weight capacity: 60 kg
 Working Radius: 2500 mm
 Vertical Lift: 1600 mm
 Air consumption: 21 nl/min



Forceful

Weight capacity: 450 kg
 Working Radius: 2000 mm
 Vertical Lift: 1300 mm
 Air consumption: 140 nl/min



Powerful

Weight capacity: 750 kg
 Working Radius: 2500 mm
 Vertical Lift: 1600 mm
 Air consumption: 270 nl/min



Magnetful

Weight capacity: 100 kg
 Working Radius: 3000 mm
 Vertical lift: 1800 mm
 Air consumption: 140 nl/min



Glassfull & Paneful Vacuum Gripper

Weight capacity: 450 kg
 Working Radius: 2000 mm
 Vertical Lift: 1300 mm
 Air consumption: 140 nl/min



Vacful 25 Vacful 50

Weight capacity:	25 kg	50 kg
Working Radius:	3000 mm	2500 mm
Vertical Lift:	1600 mm	1600 mm
Air consumption:	21 nl/min	21 nl/min



Bobbinful 100 Bobbinful 250 Bobbinful 450

Weight capacity:	100 kg	250 kg	450 kg
Working Radius:	3000 mm	2500 mm	2500 mm
Vertical Lift:	2000 mm	1700 mm	1600 mm
Air consumption:	140 nl/min	140 nl/min	270 nl/min



Drumful Pneumatic Gripper 180° Pneumatic Rotation

Weight capacity: 450 kg
 Working Radius: 2000 mm
 Vertical Lift: 1300 mm
 Air consumption: 140 nl/min