Since 1997



V8820 Continuous Inkjet Printer

Product Features

Smart cartridge with chips

Linux operating system, modular ink core design, easier maintenance, avoid production delay.

Multiple-files printing;

Communicate with external device and various packaging machine via RS232,

Barcodes:Code128, Code39, EAN13; Data-matrix, QR code

Convert bmp to dots in the printer, easy to edit the Logo.

Multi-language: English, Arabic, Spanish, Russian, Portuguese, French, Germany etc.

► Ideal for the food & beverage & cosmetic & pipe industry.



Printer Details

Electrionics compartment Linux operation system, 32 ARM CPU, 400MH 10" colorful touch screen, Easy-to-use Leadjet spare parts replacement easy for fast recovery from 00000000 = 00000000 : Main ink Filter Life:7500h **V** Separate design between Ink Sensor, Encoder, RS232 compartment and electronics compartment Reduce electromagnetic interference and the ink consumption Smart cartridge design,

Smart cartridge design, Intelligent management the status of consumables usage

Printer Details






√ 4 Head Valves

Faster ink Stop/Supply, prevent from ink leakage due to unexpected power failure

- New Design nozzle engine, Reduce the blockage probability
- V Heating Printhead & Auto Viscosity Adjustment
 Better suitability in different temperature, prevent condensation,
 keep printhead dry & clean



Parameters

Line Speed Capability Can print 1-3 lines, 300m/min(5*7 dots)

Font Matrix Configuration

Single-line:5*5, 5*7, 8*12, 11*16, 17*24, 25*25 Standard (Optional:34*34 dot) Twin-line: 5*5, 5*7, 8*12, 12*12 Tri-line: 5*5, 5*7, 8*8 Quad-line:5*5

Bar Codes:

Code128, Code39, EAN13; QR Code, Datamatrix

Character Height 1.5mm-20mm. Best:10mm Maximum can be widened 9 times

Print Distance 30mm Max. From print-head bottom to printing surface

Display 10' capacitive LCD touch screen

Memory Capacity Unlimited, based on memory card

Language

Multilingual. English, Spanish, Russian, Arabic, Persian, Portuguese, French, Germany, etc.

Custom Logo/Graphics

Can be created and covert bmp to dots on printer via USB

Data Interface USB, Sensor, RS232,

Printhead Umbilical Ultra flexible, Length:2.7m, can be customized

Printhead


Heated printhead Nozzle:60µm standard. 70µm /50µm (optional)

Fluids Containers Smart Cartridge, Ink/ Make-up (700ml)

Ink Color and Type Black, blue, red and yellow etc., dye-based ink

Electrical requirements AC100-220V, 50/60Hz, 100W.

110V~380V(Optional)



Applications



Leadjet Products



Wuhan Leadjet Science and Technology Development Co.,Ltd Add: Building 5-1, Hangang Jintan Technology Industry park, Jintan Road, Dongxihu, Wuhan 430030, Hubei, China.

www.justleadjet.com

