



Coding Excellence




期至 2014-03-19



- Full print capabilities including: alpha numerics, logos, graphics and variety of linear and 2D Datamatrix and QR codes; multiple languages; bold; upper and lower case; reverse and inverted printing; rotated character (tower) printing; variable character height and width; sequential numbering; forward & backward counting; continuous print capability
- ciPrecisionPlus optimized speed and print quality settings via smooth step control for accurate drop placement
- High speed printing of up to 9.8m/s even faster with Micro (10.3m/s) and HS50 (10.6m/s)





31 PIXEL 12PIXEL 3PIXE 3PIXE SPIXE S

Citronix Inc. BEST BEFORE: 18 APR 2030

2PIXEL PPIXEL PPIXELLINE 1 SPIXELLINE 1













QR CODES MICRO OR CODES \$¢£€¥ ÅÆË™ŸDÏ\$AÊÜÖ®®¼½¾ÄÀÝ@&#

Representative print quality only - dependent on application and substrate



Citronix Inks

Citronix offers a comprehensive range of MEK, Acetone and Ethanol based inks, make up and cleaning solvents, specially developed for use with ciSeries printers.

Citronixinks offer excellent adhesion characteristics on a variety of different substrates with immediate and quick dry inks to suit most applications.



General Purpose MEK

- Black
- Red
- Blue

Inks for Difficult Substrates

- Acetone/Ethanol Black
- Plastic
- Plastic Plus

High Contrast Pigmented Inks

- Pigment Yellow (MEK)
- Pigment Yellow (Acetone
- Pigment Black (MEK)
- **Heavy Pigment White** (Acetone)

FDA Approved Food Grade

- Food Grade Red
- Food Grade Blue

Caustic Washable

- Caustic Washable Black
- Caustic Washable Green

Specialty Inks

- Acetone Black
- Ethanol Black
- **UV** Readable
- Alcohol Resistant Black
- Thermochromic Black to Red

Citronix is a leading global supplier of continuous inkjet printers.

The ci5000 Series printer is the latest evolution of the Citronix printer range. It continues to build on our core values of Simple, Capable, Reliable and Excellent Value and reaffirms our position as a leading continuous ink jet manufacturer. Citronix printers are designed to meet some of the most demanding coding and marking applications across industries such as food and beverage, extrusion, cable and wire, cosmetics, pharmaceutical and health care, electronic components, automotive, construction and other industrial sectors.

Citronix's range of printers apply identifying marks such as best before dates, traceability codes, logos and batch codes at very high speeds to almost any kind of material or surface whether plastic, metal, paper, wood, glass or other substrate type. ciSeries printers are reknowned globally for their Simplicity, Reliability, Capability and Excellent Value.

ciSeries Product Range



ci5200

Entry level printer for typical 1 or 2 line printing applications at speeds of up to 6.9m/s. Designed with IP55 rated black powder coated steel cabinet with standard communication features configured for general purpose inks.



ci5500

Advanced high performance printer with all the capabilities of ci5300 plus advanced connectivity features such as ciLink and capability to print up to 5 lines of text, graphics and bar codes at high speeds.



Intermediate printer in stainless steel cabinet to meet 1 to 3 line printing applications with Macro and Normal drop size at speeds of up to 9.8m/s. Designed for all non-pigment ink types.



Harsh environment IP65 printer with positive air pressurized enclosure and printhead for extreme dust or washdown environments. Includes all features and capabilities of ci5500.

Specialist printers - ci5500 and ci5650

- Pigment: For high contrast printing on dark surfaces or adhesion to complex substrates
- Heavy Pigment: For white, low VOC ink for excellent contrast on dark surfaces
- Micro: Designed with 40 micron nozzle for printing very small characters (0.6mm to 6mm)
- HS50 (High Speed 50 Micron): Designed with 50 micron nozzle for extra high speed applications







Simplicity

- Easy to use intuitive touch screen graphical user interface reducing need for operator training
- Large 10" capacitive touch screen with toughened glass for industrial environments
- Single start/stop button to ensure correct shutdown and reliable start up
- Intuitive GUI with easy to use set-up wizards and quickly accessible online help database

- Simple WYSIWYG message creation and editing with drag and drop field based structure
- Multiple operator languages and character sets readily accessible
- Easy, error-proof fluids refill system no need to open printer



Capability

- Superior print quality from 1 to 5 line printing of alpha numerics, logos, graphics, and a variety of linear and 2D Datamatrix and QR codes
- High speed printing of up to 9.8m/s
 even faster with Micro (10.3m/s)
 and HS50 (10.6m/s)
- Quick installation with accessory connectors as standard – photocell, encoder, beacons
- Direct to board Ethernet connection or RS232 as standard for networking of printers
- Comprehensive range of printers with common electronics and software for all printing requirements
- Fast, simple backups, restores and pc free firmware upgrades with USB and SD ports as standard






- ciLink on board web browser interface for remote access and control of printers
- PixelPlus unique software feature to change between small and large drops (60 and 75 micron) at a touch of a button



MK JET PRINTERS ECTRONIX INC

Reliability



- IP55 washdown protection as standard.
 IP65 dust protection with ci5650
- SmartFlush an automatic printhead cleaning process that means you start first time, every time
- Simple, compact and robust industrial design

- Designed and manufactured for industrial level robustness, low parts count and serviceability
- Supported globally through a network of factory authorized and trained distributors
- Efficiently designed and manufactured in the U.S.A
- ciSafeFill fast, simple way to optimize performance, increase uptime and printer life by ensuring fluid-printer compatibility







Excellent Value

- ciEasyServ maximize printer performance, life and uptime with simple, no mess/no fuss, technician free, service module replacement
- Excellent value for feature rich printer with extended warranty
- Service intervals of 18 months or 8,000 hours to reduce planned downtime
- No expensive ink modules to replace no ink thrown away during ink replenishment
- No waste no partially filled hazardous bottles to dispose of
- Simple to diagnose and repair no need to replace expensive modules





*30m warranty for hardware from date of manufacture. Local conditions may vary

Technical Specifications

Dimensions (inches / mm)

Front View




16" (406mm)

Side View



Printhead



Operations

- 10.1" color display, capacitive touch screen
- WYSIWYG onscreen message editing with drag and drop field positioning
- Intuitive GUI with easy to use set-up wizards and quickly accessible online help database
- Single start/stop button to ensure correct shutdown and reliable start up
- Graphical user interface and messages available in multiple languages
- Dynamic message storage (over 1,000 messages)
- Real & expiration time and date; shift and rollover functions; product and batch counting; programmable password security; automatic diagnostics; event log; service reminders; backup/restore functions; downloadable software updates
- Service intervals of 8,000 hours or 18 months, depending on environment
- Fast, simple backups, restores and expandable memory with USB and SD Card ports as standard

Other Characteristics

- · Integrated, no mess, no fuss service module
- · Correct type / in-date fluid verification
- Flexible 2.7m printhead conduit (4.6m option)
- · Connectors as standard for photocell, encoder, and beacon
- · Ethernet and RS232 connectivity
- · Rugged stainless steel printhead (0.9kg)
- 750ml error-proof ink and make up bottles
- 1.9 liter ink tank; 2.25 liter make up tank
- Operating temperature range: 5-45°C (41- 113°F), ink dependent
- Humidity: 10 90%, non-condensing
- Power: 100 240V:3A, auto-ranging; 50 60Hz

Optional Accessories

- Alarm Beacons
- · Photocells
- · Shaft Encoders
- Snart Encouers
 Positive Air Kit
- · Bench and Floor Mountings
- Printhead Wash Station
- Right Angled Printhead
- Printhead Brackets

	ci5200	ci5300	ci5500	ci5650
Lines of print	1 to 2	1 to 3	1 to 5	1 to 5
Character height *	3 – 12mm	1.5 – 12mm	1.5 – 12mm	1.5 – 12mm
Font height	5 to 16 dots	5 to 25 dots	5 to 31 dots	5 to 31 dots
Drop size	Macro (75µ)	Normal (60µ)	Normal (60µ)	Normal (60µ)
		Macro (75µ)	Macro (75µ)	Macro (75µ)
PixelPlus		Yes	Yes	Yes
ciPrecisionPlus	Yes	Yes	Yes	Yes
Line Speed **	up to 6.9m/sec	up to 9.8m/sec	up to 9.8m/sec	up to 9.8m/sec
ciLink			Yes	Yes
SD, USB, RS232 and Ethernet	Yes	Yes	Yes	Yes
Inputs (photocell / encoder / message select)	1/1/0	2/1/8	2/1/8	2/1/8
Outputs (programmable alarms / relay)	3/1	3 / 1	3 / 1	3 / 1
SmartFlush	Yes	Yes	Yes	Yes
Cabinet	Powder Coated Steel	Stainless Steel	Stainless Steel	Stainless Steel
IP Rating	IP55	IP55	IP55	IP65
Weight including printhead	18.0 kg	18.0 kg	18.0 kg	18.73 kg

^{*} Minimum height (5 drop), maximum height (16+ drop). Legible at 20mm height. ** Based on 5 drop font at 50dpi.

For detailed specifications on Pigment, Heavy Pigment, Micro and HS50 printers see www.citronix.com.

Citronix Inc.
2241 S. Watson Road, Suite 111
Arlington, Texas 76010
United States of America

Tel: +1.817.633.3200 Fax: +1.817.633.3207



www.citronix.com