



Technical Data Sheet

Topadd™ TL-60A

Description

Internal Lubricant TL-60A is based on neutral dicarboxylic acid ester of saturated fatty alcohols.

Tech Spec:

Specification	Unit	TL-60A
Appearance	--	light yellow or milk-white Flake
Density	g/cm3	0.860-0.890
Acid value	mg KOH/g	<10
Iodine value	g/100g	<1
Viscosity	mPa. S(80°C)	10-16
Refractive index(80°C)	--	1.453-1.463

Comparison:

GRADE	Henkel
TL-60A	G-60

Application:

TL-60A is specially used in transparent pvc products . Dosage is about 0.3-1.0 phr.

Package and Storage:

20kg net in Paper bag with pe liner

It is not dangerous cargo .You should handle the material according to the instruction described on MSDS.The MSDS is available from sales department once required.Our regular mark is printed on the surface of package in advance .You should inform our sales person in advance If you don't need this or have any special demand for mark

+86-536-8206760 info@novistagroup.com www.novistagroup.com

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.