



## PE/PP木塑型材生產線

PP/PE WPC Profile Production Line

該生產線可連續穩定生產中空或實心的PE/PP木塑發泡型材。具有防火、防水、防腐蝕、耐潮濕、不被蟲蛀、不長真菌、耐鹼、無毒害、無污染等優良性能。主要用於生產園林景觀類、室外景觀、托盤等戶外木塑型材。配共擠機可生產共擠地板 在線壓3D木紋。

The PE/PP WPC profile extrusion line is suitable for producing the hollow/ solid PE WPC profiles. This profile has the advantage of fireproof, waterproof, anticaustic, moistureproof, mothproof, mildewproof and environment friendly. It is mainly used for extruding outdoor decorative WPC profile. Such as garden landscape, outdoor landscapes, pallets, etc, Customers can choose co-extruder and online embossing machine to achieve 3D pattern performance .



### Main Technical parameter: 主要技術參數

model	SJMS-51/105	SJMS-65/132	SJMS-80/156	SJ35/28
Max. Product width	200mm	250mm	400mm	
Extruder capacity	100-120kg/h	150-180kg/h	350-380kg/h	15kg/h
Main motor power	22kw	37kw	75kw	5.5kw
Vacuum pump power	3kw	7.5*5.5kw	11*7.5kw	
Calibrating platform length	4000mm	6000mm	6000mm	

## PP/PE木塑造粒機

PP/PE WPC Parallel Double-screw Granulating Machine

該生產線可連續穩定生產PP/PE木塑顆粒，其設備優點為高剪切、高塑化，可使塑料與木粉以及助劑充分融合。所有原材料經造粒機加工製成顆粒後，再經木塑型材生產線加工出木塑型材

This production line is suitable for producing PP/PE WPC granule. The machine adopt high quality parallel double screw extruder, it can help the plastic completely be merged with wood and chemical additives and it has the advantages of high output and good plasticization. The PP/PE WPC granules are used to produce the WPC profiles, which ensure the products more durable.

### Main Technical parameter: 主要技術參數

Model	SJMS-65	SJMS-75	SJMS-95
L/D Ratio	40: 1	40: 1	40: 1
Extruder capacity	200-220kg/h	300-350kg/h	500-600kg/h
Main motor power	75kw	90KW	132kw
Rotating speed	500rpm	500rpm	500rpm
Materials	PP/PE +Wood powder+chemical additives		
Max wood percentage	≤80%		

