

## MOUNTED CULTIVATOR WITH SPRING LOADED TINES



Figure shown, Type: Ce09

SPECIFICATIONS				
TYPE	NUMBER OF TINES	WORKING WIDTH	WEIGHT (APPROX)	POWER REQUIRED
Ce15	15	375 cm	490 Kg	90-130 HP
Ce13	13	325 cm	410 Kg	70-110 HP
Ce11	11	275 cm	350 Kg	50-90 HP
Ce09	9	225 cm	280 Kg	40-70 HP
Ce07	7	175 cm	210 Kg	30-50 HP
Ce05	5	125 cm	140 Kg	20-40 HP

COMMON SPECIFICATIONS	
DISTANCE BETWEEN ADJACENT TINES (MAX)	25 cm
WORKING DEPTH	22 cm
UNDER FRAME CLEARANCE	52 cm
TRACTOR 3-POINT HITCH COMPATIBILITY	Category 1S and/or Category 2

We reserve the right to change any information on this brochure without prior notice.

ANIZ Tarim Endustri Ic ve Dis Ticaret Ltd.  
Musallabaglari, Cakirli Caddesi 56  
42110 Selcuklu  
Konya, Turkey

Phone +90 (332) 236 0578  
Fax +90 (332) 236 7905  
<http://www.aniztarim.com.tr>  
[info@aniztarim.com.tr](mailto:info@aniztarim.com.tr)

## MOUNTED CULTIVATOR WITH SPRING LOADED



Figure shown, Type: Ce09

Tractors fitted with hydraulic lift, operate the mounted type cultivators.

A rectangular frame of angle iron on which a tube supports by means of transverse webs is mounted on three point hydraulic linkage of the tractor.

The cross members carry the tines in two staggered lines.

Depending upon the type of soil and crop, shovels are chosen for use on the cultivators.

Cultivator with spring loaded tines consist of a tine hinged to the frame and loaded with a spring so that it swings back when an obstacle is encountered.

Each of the tine of this type of cultivator is provided with two heavy coil springs, pre-tensioned to ensure minimum movement except when an obstacle is encountered.

The springs operate, when the points strike obstacles like roots or large stones, by allowing the tines to rideover the obstruction, thus preventing damage.

On passing over the obstruction, the tines are automatically reset and work continues without any interruption.

The tines are made of high carbon steel and are held in proper alignment on the main frame members.

This type of cultivator is particularly recommended for soils which are embedded with roots, stones or stumps.

ANIZ's Ce series cultivator is designed for toughest operations, used for loosening and aerating soil to a depth of 22 cm, prepares seed beds quickly and economically.

We believe it will meet expectations of both you and your customers.