

# MEDRAG-PVA01

## Technical Specifications

- Build-in Vacuum Pump
- Safe and Precise Aspiration
- Adjustable Vacuum Pressure
- Vacuum Gauge
- Fully adjustable vacuum pressure, with a conveniently located pressure gauge that shows the vacuum level at all times. The user can easily press button to activate the vacuum.
- The collection bottle incorporates a reliable overflow protection valve that closes off the tube to the vacuum in the event of a full bottle.
- In additional, the replaceable in-line filter protects the vacuum pump from contaminants and any moisture that comes through the bottle. Graduations on the collection bottle indicate the amount of fluid collected and when its ready to emptied.

For more information,  
visit our website: [www.oxivent.com.tr](http://www.oxivent.com.tr)



Turkey

Discover  
the potential

modülgrup  
MÜHENDİSLİK LTD.ŞTİ



# Technical Specifications

Property	Value / Description
Max. Flow Rate	30 liters / min
Vacuum Range	50mmHg-600 mmHg
Noise Level	65 dB
Dimensions	239(w) x 159(h) x 117(D) mm
Weight	3.96 kg ( bags and accessories included )
Electrical Requirements	12VDC 4A 60W
Battery	5200 mAh, integrated rechargeable battery
Working Time on Battery	45 minutes
Collection Bottle Capacity	1000 ml (cc) Disposable or Reusable
Operating Temperature Range	-0,4°F (-18°C) to 140°F (60°C)
Operating Relative Humidity	0-95%
Operating Atmospheric Pressure	10.2 Psi (70 kPA) - 15.4 Psi (106 kPA)
Storage and Transport Temperature Range	-0,4°F (-18°C) to 140°F (60°C)
Storage and Transport Relative Humidity	0-95%
Storage and Transport Atmospheric Pressure	7.3 Psi (50 kPA) - 15.4 Psi (106 kPA)
Accessories	1,2 liter reusable transparent break-resistant graded polycarbonate collection bottle, Disposable bacteria filter, non-metallic pharyngeal suction tip, Silicone tubing, 12 V Car Charger Kit