
 The **DRS-OT10** is provided with standard Ethernet connection to trace storage cycles. Our software application (optional) permits to check continuously all the events during the storage process, besides consultation and print-out of the internal archive.

The system is completed by a built-in printer (optional) with which several copies of the same cycle can be printed.

+ other available models

- DRS-OT10** (single door - with display)*
- DRS-OT10-P** (pass-through - with display)*
- DRS-OT10-L** (single door - without display)*
- DRS-OT10P-L** (pass-through - without display)*

*Dimensions W 720 x D 610 x H 1850 mm

 **Alarm system through operator recognition**

In the event endoscopes are removed without authorization (operator ID) the system generates warnings at the facility where it is installed. (It also works independently, e.g. acoustic signal).

The instruments are connected to the **DRS-OT10** cabinet through connection kits (optional), making it compatible with the most important endoscope brands available on the market.



DRS-OT10™

cabinet for the aseptic storage of 10 flexible endoscopes and TEE probes validate up to 800 hours

- + Fully compliant with EN 16442:2015**
- + Bacteria and viruses removal through Plasma technology**

Vers. 3/2024



MDG ENGINEERING S.r.l.
 Carraia Baruzzi, 4/M - 48123 Mezzano Ravenna (Italy)
 Tel +39 0544 1826013
 Fax +39 0544 1826015
 www.mdg-engineering.com - info@mdg-engineering.com
 Company subject to management and coordination of Medical Devices Group S.r.l.



DRS-OT10™

Cabinet for the aseptic storage of flexible endoscopes and TEE probes up to 10 horizontal positions

The **DRS-OT10** is a storage cabinet for endoscopes fully compliant with standard **EN 16442:2015 up to 800 hours of storage.**

It preserves the correct sterile air flow pressure inside in every condition avoiding contaminations, foundation of the norm itself. The cabinet is managed by a PLC through a 7" 16:9 HD touch-screen display.

The instruments are placed horizontally in

removable ABS trays up to 10 positions.

Trays are equipped with automatic connection to medical-grade air (produced by the internal compressor optional, or by the hospital supply), to dry endoscopes channels.

All our models of single-door cabinets are already prepared to become, later, two doors pass-through cabinets.

All this is possible thanks to a special modification



PASS-THROUGH VERSION



RACK10
Trolley entirely made in SAE 304 stainless-steel born to transport endoscopes. It can contain up to 10 trays



INTERNAL COMPRESSOR
(optional)

MEDICAL - GRADE AIR CONNECTION

ETHERNET CONNECTION

BUILT-IN PRINTER

COLOUR TOUCH-SCREEN
display 7" 16:9 HD

WIRELESS BARCODE GUN
(RFID optional)

USB PORT

10 TRAYS IN ABS
removable and traceable for positions and numbers

DIMENSIONS:
W: 720 MM
D: 610 MM
H: 1850 MM

The **DRS-OT10**, through the medical-grade air connection and the self-produced air (internal compressor - optional) ensures in each condition a **barrier against viruses and bacteria**, this thanks to the **0,2 micron H14 HEPA filter to dry endoscope** externally and the **0,003 micron absolute filter** to dry endoscopes internally.

The **patented plasma sanitification system** is involved in this system, too.

It is built-in in the recirculation of the air; it avoids environmental contaminations due to load and unloading of instruments.

The forced air-heating system up to 30°C allows a safe and rapid drying.

