



ATS LED 700 -700

Characteristics	Özellikler	700 dome	700 dome
• Field diameter(mm)	Aydınlatma Çapı	120-260	120-260
• Brightness Dimming Level	Parlaklık Seviyeleri	1%-100%	1%-100%
• D50 / D10		0.51	0.51
• Illumination Depth 20%(mm)	Aydınlatma Derinliği	≥600	≥600
• CRI (%)	Renk İndeksi	≥85	≥85
• Illumination (lux) Adjustment	İluminasyon (Lüks)	40000-160000	40000-160000
• Color Temperature (K)	Renk Isısı	4000-5500	4000-5500
• Lamp power	Lamba Gücü	70VA	70VA
• Voltage	Voltaj	AC 100V-240V	AC 100V-240V
• Frequency	Frekans	50/60Hz	50/60Hz
• LED Quantity	LED Adedi	80	80
• Lighting Mode	Işık Modları	Standard-Endoscope-Low Lighting	
• LED Lifespan (hours)	LED Ömrü (saat)	≥50000	≥50000
• Working conditions	Çalışma Koşulları	5°C~40°C, 700hPa-1060hPa, 10%- 80% RH	
• Light head thickness(mm) ±5	Lamba Kalınlığı	104	104

ATS LED 700 M (Mobile)

