

HAORUN MEDICAL PRODUCTS CO., LTD

Professional Manufacturer of Disposable Medical Products

What can we support?

- Raw materials supply
- Semi-finished products supply
- Machines supply

HEALTHCARE WITH YOU

www.haorunmed.com



Raw materials supplying

Raw materials for gauze Raw materials for bandages


- > Raw materials for Wound plaster
- Raw materials for Medical Tape
- Raw materials for Wound Dressing
- Raw materials for Capsicum Plaster/ Perforated Plaster Roll
- Raw materials for Alcohol Pad
- Packaging materials for Cooling patch
- Raw materials for Cohesive Bandage
- Raw materials for Face mask



Raw materials for Wound Plaster

Release paper





Basic fabric



Packaging paper





Absorbent Pad





Cold seal paper & film for wound plaster

Jumbo roll	Width	Length	Diameter
Medical cold seal paper white (latex)	45mm/88mm/95mm/customized Max: 970mm	2000m	36cm
I Medical cold seal paper printed (latex)	45mm/88mm/95mm/customized Max: 780mm	2000m	36cm
I Medical fransparent cold seal film (latex)	45mm/88mm/95mm/customized Max: 970mm	2000m	36cm
I Medical cold seal paper white (latex tree)	45mm/88mm/95mm/customized Max: 585mm	2000m	36cm
I Medical cold seal paper printed (latex tree)	45mm/88mm/95mm/customized Max: 585mm	2000m	36cm
Medical transparent cold seal film (latex free)	45mm/88mm/95mm/customized	2000m	36cm
Medical hot seal paper	45mm/88mm/95mm/customized	2000m	36cm

Specification: 40g+4g/m²(latex), 49g+6g/m2(latex free)

Package:5 rolls/ctn











Release Paper

Name: Release Paper(Glassine Silicone Coating)

Weight:65g/m2,80g/m2,100g/m2

Specification : Customized

Release: 0.08-0.12N/25cm

Jumbo roll	Width	Length	Diameter	Application	
Release paper 65g				Wound plaster	
Release paper 80g	25mm/51mm/43m m/customized Max: 1030mm	1000m	I 1000m I	26cm - 31cm	Wound dressing/Perforated roll
Release paper 100g	wax. 1000mm		3 TOTT	Wound dressing/Chili plaster	





Package:10rolls/ctn 20rolls/ctn





Absorbent Pads for wound plaster

Weight	Decription	Width	Length	Absorption	Diameter
70g	White Spunlaced nonwoven				
70g	Yellow Spunlaced nonwoven				
70g	Yellow Spunlaced nonwoven with punch holes				
90g	White Needle punched non woven with one side PE film coated				
110g	White Needle punched non woven with one side PE film coated		200m	> 500 36	36-41cm
110g	Yellow Needle punched non woven with one side PE film coated	1.5cm/2.0cm/2.3 cm/customized			
110g	0.1% Benzalkonium chloride yellow spunlaced non woven with one side yellow PE film coated				
110g	Yellow gauze				
120g	White Needle punched non woven with one side PE film coated				
120g	Brown color				
180g	Metal detectable				







Discription: Absorbent Pad 110g±5g/m² Size: 25mmx200m Qty: 10rolls MFG: 2021-05-10 Package: 10rolls/ctn; 20rolls/ctn





Absorbent Pads

Description: Spunlaced nonwoven absorbent pad

Weight: 70g spunlaced nonwoven with punch holes

70g spunlaced nonwoven without punch holes 90g/110g needle punched nonwoven with PE film 110g yellow gauze

Absorption : ≥500%

Application: for wound plaster











Absorbent Pads

Name: 0.1%Benzalkonium Chloride Absorbent Pad

Material: Spunlance nonwoven+PE film

 $\textbf{Weight:} 90g/110g/m^2$

Absorption: ≥500%

Application: For wound plaster's absorbent pad









Adhesive jumbo rolls for wound plaster

Material description	Coating Hotmelt	Max Width	Length	Release
120g Skin color cotton C	90g	94cm	600m	
120g Skin color cotton C	115g	94cm	600m	
110g skin color elastic fabric	65g	99cm	300m	
110g light skin color 4 elastic fabric	65g	101cm	300m	
100g skin non elasitc fabric	60g	102cm	300m	
110g pink skin elastic fabric A/B/C	65g	102cm	300m	
110g blue elastic fabric	65g	102cm	300m	PET 28g/19um, 0.08-0.12N/25mm
155g elastic heavy red cotton fabric	90g	102cm	150m	0.00 0.1217.2011111
150g non elastic heavy red cotton fabric	90g	102cm	150m	
37g skin hot rolled non woven	40g	90cm	400m	
45g white hot rolled non woven	40g	103cm	500m	
50g white non elastic spunlaced non woven	40g	103cm	500m	
50g skin non elastic spunlaced non woven	40g	103cm	500m	

- Width can be customized
- Coating: Transparent hotmelt/Zinc oxide hotmelt/customized
- Package: 5rolls/ctn/customized
- We also supply materials only without adhesive







Adhesive jumbo rolls for wound plaster

Material description	Acrylic Coating	Width	Length	Release
53g skin color PE	33g	100cm	500m	
60g high elastic transparent PE	33g	100cm	500m	
60g skin gridding PE	33g	100cm	500m	
60g brown spot PE	33g	100cm	500m	
60g blue PE	33g	100cm	500m	PET 34g/23um,
Cartoon printed PE	33g	100cm	500m	0.08-0.12N/25mm
110g skin color elastic fabric	55g	99cm	300m	
50g white non elastic spunlaced non woven	40g	103cm	500m	
50g skin non elastic spunlaced non woven	40g	103cm	500m	
PU Transparent film 20um	35g	100cm	500m	

- Width can be customized
- Weight of Coating: can be customized
- Package: 5rolls/ctn/customized
- We also supply materials only without adhesive





Description: Elastic /non elastic fabric

Specification:

110g/m2 blue/skin elastic fabric + hotmelt+34g/23um PET film 110g/m2 blue/skin elastic fabric+acylic+28g/19um PET film 100g/m2 non elastic fabric + hotmelt+34g/23um PET film

Application: For fabric wound plaster











Description: Skin/white hot rolled non woven fabric

Specification:

37g/m2 skin fabric + hotmelt+34g/23um PET film 45g/m2 white fabric+ hotmelt+34g/23um PET film

Application: For wound plaster











Description: Skin color gridding/spot PE

Specification: 60g/m² PE film + Acrylic + PET 34g/23um **Application**: For transparent PE waterproof wound plaster











Description: Skin color / Blue PE

Specification:

 $53g/m^2$ skin PE film +Acrylic + 34g/23um PET film $60g/m^2$ blue PE film +Acrylic + 34g/23um PET film

Application: For PE waterproof wound plaster











Description: Transparent PU

Specification: 20Micron TPU+30Micron PET+ Acrylic

Moisture Proofness:800g(m²/24h)

Application: as a basic film for wound plaster/wound dressing

pad/wound dressing roll









Description: Transparent High Elastic PE

Specification: based on customer's requirement **Weight**: 60g/m² PE film + Acrylic + PET 34g/23um

Application: For transparent PE waterproof wound plaster











Description: PE adhesive film with printing

Specification: 60g/m² PE film+ Acrylic+PET 34g/23um


Application: For cartoon printed wound plaster







Raw materials for Wound Dressing Pad



Release Paper

Name: Release Paper(Glassine Silicone Coating)

Weight:65g/m2,80g/m2,100g/m2

Specification: Customized **Release**: 0.08-0.12N/25cm

Jumbo roll	Width	Length	Diameter	Application
Release paper 65g				Wound plaster
Release paper 80g	25mm/51mm/43m m/customized Max: 1030mm	1000m	26cm - 31cm	Wound dressing/Perforated roll
Release paper 100g	iwax. 1030IIIII		310111	Wound dressing/Chili plaster





Package:10rolls/ctn 20rolls/ctn



Absorbent Pads for wound dressing pad

Weight	Description	Width	Length	Absorption
150g	White Needle punched non woven with one side PE film coated	5cm-30cm/customized	150m	> 500
180g	White Needle punched non woven with one side PE film coated	5cm-30cm/customized	150m	> 500
200g	White Needle punched non woven with one side PE film coated	5cm-30cm/customized	150m	> 500
200g	Brown color	5cm-31cm/customized	150m	> 500
220g	White Needle punched non woven with one side PE film coated	5cm-30cm/customized	150m	> 500
250g	White Needle punched non woven with one side PE film coated	5cm-30cm/customized	150m	> 500
280g	White Needle punched non woven with one side PE film coated	5cm-30cm/customized	150m	> 1000









Packing Paper for Wound Dressing Pad

Name: Medical Dialysis paper

Description	Width of roll	Length	Sealing temperature
65g Medical Dialysis paper/coated white paper	120mm-400mm/customized		
58g PE coated paper	120mm-400mm/customized	1000m /roll	130-160 °C
Composition transparent film(PE/PET)	120mm-400mm/customized		

• Sealing temperature can adjust according to equipment











Basic fabric for Wound dressing

Application: Nonwoven Wound dressing
PU wound dressing
Eye pad/IV dressing

Description	Glue	Max Width of roll	Length of roll	Release
50g white non elastic spunlaced non woven	40g hotmelt	103cm	500m	PET 28g/19um, 0.08-0.12N/25mm
50g white non elastic spunlaced non woven	40g hotmelt	103cm	500m	60g release paper
PU Transparent film (20um PE/30um PET)	25g acrylic	100cm	500m	PET 34g/23um, 0.08-0.12N/25mm
PU Transparent film (20um PE/30um PET)	25g acrylic	100cm	500m	60g release paper







Back

We can also supply fabric without coating glue

Jumbo rolls for adhesive medical tapes













Description	Weight of Acrylic	Max width of roll	Length	Release
26g(+10g silicone) White non woven 3M	35g	100cm	500m	
26g(+10g silicone) Skin non woven 3M	35g	100cm	500m	
65g perforated transparent PE	28g	77.8/78cm	500m	DET 24a/22um
75g perforated transparent PE	30g	77.8/78cm	500m	PET 34g/23um, 0.08-0.12N/25mm
80g perforated transparent PE	28g	77.8/78cm	500m	
100g perforated transparent PE	33g	77.8/78cm	500m	
60g vein non woven+90g silicone	90g	108cm	500m	
60g vein non woven+ acrylic	?	108cm	500m	



We also can supply materials without adhesive.

Jumbo rolls for medical tapes

Big Jumbo Rolls



Log rolls



Loading with pallets



Loading without pallets






Semi finish products for Capsicum plaster/Perforated plaster roll

Perforated Cotton jumbo rolls

Release paper

Adhesive











Raw materials for Capsicum plaster /perforated plaster roll

	Weight of glue		Length	Release paper	Application
120g skin color cotton	75g	10/12/18cm	300m		Perforated plaster
120g skin color cotton	105g	10/12/18cm	300m	80g/100g release paper 0.45-0.6N/25mm	Capsicum plaster
124g white color cotton	90g	10/12/18cm	300m		Capsicum plaster



Packing materials / Jumbo rolls	Width of Roll	Length of Roll
80g Pearlescent printed packaging	32cm/36cm/Customized	1000m
82g coated paper printed packaging	32cm/36cm/Customized	1000m







Hotmelt Adhesive

Description: Transparent/Zinc oxide/Customized)

Package: 25kg/ctn;20kg/ctn

Recommended operating temperature: 140°C to 180°C, depending on machine, substrate, environment and other conditions

Softening Point

Approx. 98°C, Universal method

Product specifications

Viscosity: 5000-10000cps

Softening point: 90.0-110°C

It is a hot-melt pressure-sensitive adhesive suitable for bandaids, medical tapes and bandages. It has the characteristics of moderate adhesion and no residue.







Packing materials for alcohol pad

Specification: Spunlaced Non woven fabric

Width:6cm/10cm/12cmx800m/customized

Weight:40g/45g/50g

Non woven fabric







Aluminum foil paper

Specification: 40cm/36cmx1000m per roll

Weight:73g/m2

Composition: Paper/PE/Aluminum Foil/EAA



Packaging materials for cooling patch

Material description	Width of roll	Photo
103g Aluminum paper composition film	196mm	COOLINGGEL
80g PET Aluminum film	196mm	
42g Transparent film	490mm	
100g Non elastic non woven fabric	490mm	



Jumbo rolls for cohesive bandage



Materials: Non-woven+ Spandex

Big Jumbo Roll Size: 1.05-1.08m* 1000m ± 10 m

Dia: 75-80cm

Weight: 75-80Kg

Package:

1. Isolating membrane every layer

2. Wrapped with woven bag



Log rolls



Jumbo rolls for cohesive bandage

Materials: Non-woven+ Spandex

Jumbo roll	Package	Meas.	G.W	
108cmx4.5m	36rolls/ctn	38*38*112	12.5KG	
72cmx4.5m	36rolls/ctn	38*38*82	10.5KG	
22cmx4.5m	64rolls/ctn	46*46*27	4.5KG	









Melt blown non woven fabric

Description: Electrical Electret Melt blown non woven

Specification:17.5cm/26cm (Customized)

Fabric weight:25g

Application: YY/T0969, YY0469, GB2626,KN95

Description: Water Electret Melt blown non woven

Specification:26cm (Customized)

Fabric weight:25g

Application: EN149 standard/ FFP2 FFP2 FFP3 mask







SS Non woven fabric

Name: SS Hot rolled non woven

Description: 18.5cm (customized)

Weight:25g (customized)

Application: non woven face mask







Products - Face Mask

- Surgical Face Mask/ Child Mask
- KN95 Respirator
- FFP2 Respirator
- Production Lines: 22
- Daily Productivity: 1.5M pieces

STANDARDS:

EN14683:2019 TYPE IIR

GB2626-2016

EN149:2001+A1:2009

ASTM F2101-2019 (Level 2)

510K Number













High speed production machine for wound plaster





Item No: MAC-001

MAX.size of masterial roll	380MM
MAX.width size of the material tape	85MM
MAX.size of the plaster	78MM
Plaster Orientation	NO
MAX.size of the wrapper paper	95MM
Produce Speed	0—720PCS/MIN
Wrapping Paper Orlentation	NO
Machine Power	3.5KW
Power Voltage	380V
Machine size	2800*750*1900
Machine Weight	1500KGS



Hotmelt coating machine



	ion of the hot melt coating r	nachine
Stylle	THB-560	THB-1100
The width of the coated	560mm	1100mm
Amount of glue	20-2	200g
Coating speed	0-6	-Om
Unwinding diameter	1000	0mm
Rolling diameter	80r	mm
The feeding device	3°air expa	nsion core
Correction device	gold med	al optional
Installed power	18kw	28kw
Electric source	38	OV
he length of he whole machine	4500mm	-6800mm
The width of the whole machine	1500mm	2000mm
The height of the whole machine	1500mm	19mm
Controlled temperature	60°C-	230°C



Item No: MAC-002





Rewinding machine



Rewinding machine main technical parameters		
Rewinding width	500-1100mm	
Maximum diameter	150mm	
Rewinding speed	150m/min	
Tube core diameter	25-50mm	
Electric tension	380V	
Power of motor	2.75KW	
The using of air pressure	2-5pa	





Cutting machine



Item No: MAC-004

The main technical parameters of automatic cutting machine		
Effective width	1000mm	
Cutting width	5-1000mm	
Tube core diameter	25-50mm	
Maximum cutting diameter	100mm	
Electric tension	380V	
The power of the whole machine	2KW	





THANK YOU!

