



Consistent, repeatable results

The HydroPro™ Plus initiates a new generation of professional sous vide immersion circulators. Featuring Sous Vide Toolbox™, an intuitive on-board guided cooking experience that simplifies sous vide cooking by using scientific algorithms to calculate time to temperature and pasteurization for a vast range of foods.

The HydroPro™ Plus includes a digital needle probe that displays the core temperature of the food in real-time, enabling delta cooking. Data is stored on-board and can be transferred to the HACCP Manager App via Bluetooth for easy logging of all your sous vide cooks.

Programming and repeatability of your cooks is made simple thanks to ‘My Presets’ and usability has been enhanced via a large touch screen that allows easy manual input of cooking parameters. The powerful heater and newly designed pumping system ensure precise temperature control across a wide range of cooking volumes.

Designed with food safety and simple maintenance in mind, the design features a smooth waterproof construction, quick-release clamp, and a magnetic impeller for easy cleaning and descaling. Removable parts are commercial dishwasher safe.

Visit www.sagepolyscience.com to learn about the entire line of Sage | PolyScience products and great recipe ideas.

Sous Vide Immersion Circulator

Technical Specifications

PERFORMANCE

Power	1485 Watts
Flow Rate	17 L/Min
Max Water Bath Size	45L with lid

DURABILITY

• IPX7 Water Resistant • NSF Commercially Certified	• Stainless Steel Exterior • Ruby Bearing • Tungsten Carbide Shaft
---	--

PRECISION

Temperature Resolution	0.1°F/0.1°C
Temperature Stability	± 0.1°F/0.1°C
Maximum Water Temperature	194°F/90°C

USABILITY

Color TFT Touch Display	360° Adjustable Flow Direction
On-board Cooking Guide Sous Vide Toolbox™	Coil-less Heating Chamber
Manual Time & Temperature Controls	Low Water Detection
Integrated Digital Probe	Magnetic Impeller Coupling
Variable Flow Speed	Adjustable & Detachable Clamp

CONNECTIVITY

Bluetooth

WEIGHTS & DIMENSIONS

Unit Weight	2kg / 4.4lb	
Unit Dimensions (L x D x H)	37.1cm x 9.3 x 17cm / 14.6in x 3.7in x 6.7in	
Shipping Weight	3.2kg / 7.1lb	
Shipping Dimensions (L x D x H)	41.5cm x 14.7cm x 25.2cm / 16.3in x 5.8in x 9.9in	
SKU Number	GSV750PSS4EEU1	Europe
	GSV750PSS4GEU1	UK

ACCESSORIES

- Adjustable & Detachable Clamp
- Magnetic Impeller
- 360° Adjustable Flow Direction Foot
- Digital Probe & Calibration Holder
- Carry Case with Handle.