

CMP 444 Continuous Motion Packaging Machine
Hareketli Yatay Çeneli Paketleme Makinesi

CMP 444 Servo Continuous Motion Packaging Machine is designed to get 130 packs/min for the weight range between 20gr – 1000gr , the size of the pack is 250*340 mm in maximum, The packs shapes can be Pillow bag, Stand up bag. This machine is designed for the facilities who desire higher speed.

The volumetric filling system and the electronic weighing system are used for crystalized and granular products, The screw filling system is used for powder products. Also there is the liquid filling systems for liquid products

CMP 444 Hareketli yatay çeneli servolu dikey paketleme makinası yastık ,ve oturan paket yapmaktadır. Makinede 20 gr ile 1000 gr arası ürünler paketlenmektedir. Max paket ebadı 250*340 mm dir.

Yüksek hızda paketleme kapasitesi istenilen tesislerde kullanılmaktadır. Makinede Volumetrik dolum sistemi serbest akıcılığı olan kristalize ve granül ürünler, Vidalı dolum sistemi ile toz ürünler Elektronik terazili dolum büyük ebatlı ve kırılğan ürünler, likit dolum sistemi sıvı ürünler paketlenmektedir.

Accessories

- Feeding Elevator
- Output Conveyor
- Printer
- Folding Unit for Standup bag
- Quadro bag System
- Metal Detector
- Checkweigher
- Dust Sucking System
- Gas Flushing System
- Anti-static bar
- Euro hole device
- Round hole Device
- Inserter cards system
- Labeling System



Technical Details Teknik Detay	CMP 444
Filling System / Dolum Sistemi	Electronic weighing system- Servo, Volumetric , Auger filler / Volumetrik, Vidalı, Çok kefeli terazili, Servo kontrollü terazili
Suitable for / Paketlenebilen ürünler	Cereals, nuts, dry fruits, chocolate, candy, chips, cookies, pasta, fruit, vegetables, frozen meat, coffee, tea etc. Kuruyemiş, şekerleme, bisküvi, çikolata, cipsler, kraker, jelly, makarnalar, kahve, krema vb. ürünler.
Filling Range / Gramaj Aralığı	20- 1000 gr
Shape of the Bag / Paket Tipleri	Pillow bag , Stand up bag / Yastık paket ve oturan paket
Packaging Speed / Paketleme Hızı	70-130 ppm / 70-130 pak/dakika
Type of Packaging Material / Ambalaj Malzemesi Cinsi	OPP, CPP, Pet, Alu, Metalize and other laminated films / Opp, Cpp, Pet, Alu, Metalize vb. laminasyonlu malzemeler
Min. Dimensions of the Bag / Min. Paket Eni ve Boyu	70 x 100 mm
Max. Dimensions of the Bag / Max. Paket Eni ve Boyu	260 x 400 mm
Max. Width of the Film / Max. Bobin Eni	550 mm
Inner Diameter of the Core / Bobin Makarasi İç Çapı	76 mm
Max . Diameter of the Roll / Max. Bobin Çapı	500 mm
Dimensions of the Machine / Makine Ebatları	1500 x 2200 x 1700 mm
Weight of the Machine / Makine Ağırlığı	1.100-kg
Mechanic Structure / Mekanik Kontrol Sistemi	By servo / Üç eksen servo kontrollü
Pneumatic Systems / Pnömatik Sistem	Festo
Control System / Elektrik Sistemi	MITSUBISHI
Electricity Supply & Consumption / Elektrik Beslemesi ve Tüketimi	380 Volt AC / 7 Kwh
Air Supply & Consumption / Hava Beslemesi ve Tüketimi	6 bar / 200 Lt / min.