




**AKPORT**  
AKPORT MAKİNE SANAYİ VE TİCARET LTD. ŞTİ.



**3 Katmanlı CO-EX Kafa,  
Döner Kule İle Yüksek Kaliteli  
Film Üretimi**



[www.akportmakine.com](http://www.akportmakine.com)

**3-Layer CO-EX Die  
Rotary Tower High Quality  
Film Production With**

**TAUREX<sup>▲</sup> CO-EX**

**SERIES 75-100-75 / 3300**

# TAUREX<sup>®</sup> CO-EX

SERIES 75-100-75 / 3300

## STANDART PARTS

STANDART AKSAMLAR

- Thermoregulation System for Extruder Feeding Zone
- İçten Balon soğutma Sistemi (IBC)
- Heat Exchanger
- Bubble Guide
- Secondary Nip
- Edge Guide
- Technical Service Support with Remote Connection
- Ekstrüder Besleme Bölgesi için Termoregülasyon Sistemi
- Internal Bubble Cooling System (IBC)
- Eşanşör Grubu
- Balon Tutucu
- Ara Çekici
- Kenar Kontrol
- Uzaktan Bağlantı İle Teknik Servis Desteği

## OPTIONAL PARTS

OPSİYONEL AKSAMLAR

- Corona Teater
- 4 Component Dosing Unit
- 6 Component Dosing Unit
- Air Ring With Tickness Control
- Hot Slitting Unit
- Korona Cihazı
- 4 Komponentli Dozajlama Ünitesi
- 6 Komponentli Dozajlama Ünitesi
- Kalınlık Kontrollü Hava Başlığı
- Sıcak Dilimleme Ünitesi



## TECHNICAL CHART — TEKNİK TABLO

|                       |                         |  |
|-----------------------|-------------------------|--|
| Useable Raw Materials | Kullanılabilen Hammadde | LDPE, LLDPE, mLLDPE, MDPE, HDPE and their mixtures                     |
| Film Width            | Film Genişliği          | minimum : 1600 mm / maximum : 3200 mm                                  |
| Film Thickness        | Film Kalınlığı          | 25 - 150 micron  |
| Maximum Capacity      | Maksimum Kapasite       | 600 kg / h   |
| Die Type and Diameter | Kafa Tipi ve Çapı       | 3 Layer Coex Die Ø600 with IBC System                                  |
| Layer Distrubution    | Katman Dağılımı         | A: %25 - B: %50 - C:%25  |
| Maximum Line Speed    | Maksimum Hat Hızı       | 150 mt / min   |
| Main Engine           | Ana Motor               | A: 75kW - B: 110 kW - C: 75kW  |
| Screw - Barrel        | Vida - Kovan            | A: Ø75 - B: Ø100 - C: Ø75<br>Bimetal plated L / D ratio 32:1           |
| Filter                | Fitre                   | A: Ø95 - B: Ø125 - C: Ø95<br>Hydraulic Screen Changer (Manual Control) |
| Tower Type            | Kule Tipi               | Rotary Tower (Döner Kule)  |
| Tower Height          | Kule Yüksekliği         | 16 mt  |
| Winder                | Sarcı                   | Double Station Non-Stop  |

**HDPE / LDPE**

**PLASTIC FILM AND RECYCLING MACHINES**  
PLASTİK FİLM VE GERİ DÖNÜŞÜM MAKİNELERİ



**WE PROCESSED  
TECHNOLOGY  
FOR YOU...**

TEKNOLOJİYİ  
SİZİN İÇİN İŞLEDİK...



**AKPORT MAKİNE SANAYİ VE TİCARET LTD. ŞTİ.**

Mermerciler Sanayi Sitesi 2. Bulvar No: 10/2 Beylikdüzü - İstanbul - TURKEY  
Tel: +90 (212) 876 53 13 / 14 Fax: +90 (212) 876 53 15  
info@akportmakine.com



**AKPORT**

AKPORT MAKİNE SANAYİ VE TİCARET LTD. ŞTİ.