



CCM PRE RINSING GLASS WASHING MACHINES



DESCRIPTION

Pre-Rinsing Glass Washing Machine is specially designed for glass processing plants. With the help of water spray nozzles in the pre-rinsing section, the glass becomes more suitable for washing. After this process, the glass is processed in the washing unit with 6 brushes and the glass is washed with maximum quality and perfectly.

MACHINES SPECIFICATIONS

Pre-rinsing process with the help of nozzles located on stainless pvc
6 pieces brush those are high sensitive in the washing unit.

Stainless steel washing unit.

Sturdy steel construction structure.

Durable conveyor tires that do not trace in glass surface

Operating direction "back and forward".

Adjustable working speed by control switch.

The water tanks (2) those produced stainless steel, with heater.

Adjustable temperature of washing water by digital indicator.

Electrostatic powder coating systems against iron oxide

Drying fan (optional : isolated cabin and dust filter).

Left to right operating direction



CCM MACHINE

www.ccmachine.com



TECHNICAL SPECIFICATIONS

1700X6 PRE-RINSING GLASS WASHING MACHINE

Processable glass dimensions (min.)	: 160x320 mm
Processable glass dimensions (max.)	: 1700x3000 mm
Processable glass thickness	: 3-12 mm
Washing Speed	: 1-10 mt/min.
Width	: 800 mm
Length	: 8000 mm
Height	: 2800 mm
Weight	: 1850 kg
Voltage	: 400 V 3NPE
Frequency	: 50-60 HZ
Total Power	: 11 Kw