

- Welded steel construction
- High carbon/high chrome, two edged top and four edged bottom blades

- Cutting beam working in perfectly sliding, durable teflon slideways
- Easy blade gap adjustment in front
- Mechanical sheet clamping system

STANDART EQUIPMENTS

- Manual backgauge with 750 mm stroke
- Squaring arm with ruler
- Foot pedal
- Cutting unit counter
- Front sheet holding arms
- Finger protection cages
- Rear protection cages with photocell
- Cutting line illumination

OPTIONAL EQUIPMENTS

- NC controlled backgauge with 750 mm stroke
- NC controlled backgauge with 1000 mm stroke
- Pneumatic sheet support system with return to rear feature
- Rear protection cages with light barrier
- 0-180° angular cutting device
- Cutting line illumination with shadow wire
- Elgo NC control unit
- Longer squaring arm and front sheet holding arms up to 3000 mm
- Front operated manual backgauge with ball screw



MODEL	Shearing Capacity Kesme Kapasitesi	Max. Shearing Length Max. Kesme Uzunluğu	Strokes Per Minute Dakikada Kesme Sayısı	Motor Power Motor Gücü	Table Height Tabla Yüksekliği	Table Width Tabla Genişliği	Backgauge Distance Arka Dayama Mesafesi	Width En	Length Boy	Height Yükseklik	Approximate Weight Yaklaşık Ağırlık
	mm	mm		kw	mm	mm	mm	mm	mm	mm	kg
SRGM-H 1360	3	1360	35	3	810	390	750	2100	1920	1260	1.250
SRGM-H 1560	3	2560	35	3	810	390	750	2100	2100	1260	1500
SRGM-H 2560	3	2060	35	4	810	390	750	2100	2650	1260	1.750
SRGM-H 2560	2,5	2560	35	4	810	390	750	2100	3150	1260	1950
SRGM-H 3060	2	3060	35	4	810	390	750	2100	3650	1260	2.200

- Kaynaklı çelik konstrüksiyon
- İki ağızlı kullanılabilen üst ve dört ağızlı kullanılabilen alt bıçaklar
- Her iki yanı uzun ömürlü teflon kızaklı üst kesici çene

- Kolay ayarlanabilir sentil ayarı
- Kesme anında sacın kaymasını önleyen mekanik baskı sistemi

STANDART EKİPMANLAR

- 750 mm stroklu manuel arka dayama
- Cetveli gönye
- Ayak pedali
- Kesim adet sayıcı
- Ön sac tutma kolları
- Parmak koruma
- Fotoselli arka muhafaza sacları
- Kesim hattı aydınlatması

OPSİYONEL EKİPMANLAR

- NC kontrollü 750 mm stroklu motorlu arka dayama
- NC kontrollü 1000 mm stroklu motorlu arka dayama
- Pnömatik arka sac destek&tahliye sistemi
- Işın bariyerli arka koruma sacları
- 0-180° açılı kesim aparatı
- Kesim hattı ışıklandırması-gölge telli
- Elgo kontrol ünitesi
- 3000 mm'ye kadar standart harici uzunlukta cetvel kolu ve ön kollar
- Önden el tekeri ile kontrol edilen vidalı millî manuel arka dayama

