



Profile Specifications



QUALIFICATION	SPECIFICATIONS	TOLERANCE
Profile Alloy	3003 Aluminum	> %99 Al
Temper	H 19 - H 26	-
Height (H1)	6,5 mm	± 0,2 mm
Height (H2)	4,8 mm	± 0,5 mm
Width (X)	5,5 mm 7,5 mm 8,5 mm 9,5 mm 10,5 mm 11,5 mm 13,5 mm 14,5 mm 15,5 mm 17,5 mm 19,5 mm 21,5 mm 23,5 mm	± 0,2 mm
Width (Y)	2,8 mm 4,8 mm 5,9 mm 6,9 mm 6,9 mm 7,9 mm 9,9 mm 10,9 mm 11,9 mm 13,9 mm 15,9 mm 17,9 mm 19,9 mm	± 0,2 mm
Profile Wall Thickness (T)	The profile wall thickness it varies from 0.18 to 0.34 mm according to the product sizes.	± 0,02 mm
Penetration Holes (Z)	The distance of the opened holes on the surface of Profile 'X' changes according to profile width.	-
Length	It is produced in a standard form of a 600 cm length.	± 5,00 mm
Surface Oil Amount	≤ 1 mg / meter	-
Merge Source	High frequency induction welding.	-
Welded Surface	This induction source it takes place on the 'Y' surface.	-
Color of Profile	Silver	-
Printing of Logo / Name	The profile is customized by printing customer's logo on the 'X' surface at equal intervals of 30 cm.	-
Packing	It is packed in standard resistant cardboard boxes or in timber crates according to the order.	-

