

## CM SERIES CULTIVATORS WITH SPRING LOADED TINES FOR SUB-COMPACT TRACTORS



Figure shown, Type: CM-07

SPECIFICATIONS				
TYPE	NUMBER OF TINES	WORKING WIDTH	WEIGHT (APPROX)	POWER REQUIRED
CM-07	7	175 cm	150 Kg	25-50 HP
CM-05	5	125 cm	110 Kg	18-40 HP

COMMON SPECIFICATIONS	
DISTANCE BETWEEN ADJACENT TINES (MAX)	25 cm
WORKING DEPTH	15 cm
UNDER FRAME CLEARENCE	42 cm
TRACTOR 3-POINT HITCH COMPATIBILITY	Category 1N and/or Category 1S

We reserve the right to change any information on this brochure without prior notice.

ANIZ Tarim Endustri Ic ve Dis Ticaret Ltd. Musallabaglari, Cakirli Caddesi 56 42110 Selcuklu Konya, Turkey	Phone WhatsApp +90 (332) 236 0578 Fax +90 (332) 236 7905 <a href="http://www.aniztarim.com.tr">http://www.aniztarim.com.tr</a> <a href="mailto:info@aniztarim.com.tr">info@aniztarim.com.tr</a>
---	--



## CM SERIES CULTIVATORS WITH SPRING LOADED TINES FOR SUB-COMPACT TRACTORS



Figure shown, Type: CM-05

Sub-compact tractors fitted with hydraulic lift, operate the CM series mounted type cultivators.

A rectangular frame of angle iron on which a tube supports by means of transverse webs is mounted on three point hydraulic linkage of the tractor.

The cross members carry the tines in two staggered lines.

Depending upon the type of soil and crop, points are chosen for use on the cultivators.

Cultivator with spring loaded tines consist of a tine hinged to the frame and loaded with a spring so that it swings back when an obstacle is encountered.

Each of the tine of this type of cultivator is provided with two heavy coil springs, pre-tensioned to ensure minimum movement except when an obstacle is encountered.

The springs operate, when the points strike obstacles like roots or large stones, by allowing the tines to rideover the obstruction, thus preventing damage.

On passing over the obstruction, the tines are automatically reset and work continues without any interruption.

The tines are made of high carbon steel and are held in proper alignment on the main frame members.

This type of cultivator is particularly recommended for soils which are embedded with roots, stones or stumps.

ANIZ's CM series cultivator is designed for toughest operations, used for loosening and aerating soil to a depth of 15 cm, prepares seed beds quickly and economically.

We believe it will meet expectations of both you and your customers.