

MOUNTED SUBSOILER



Figures shown: SS12 and SS20

MODELS	SS12	SS20	SS30
Power Rating	40-90 HP	70-110 HP	70-110 HP
Hitch Category	Category 1 & 2 3-point hitch.		
Overall Width	85 cm	150 cm	150 cm
Distance Between Shanks	-	140 cm	70 cm
Approximate Weight	140 Kg	240 Kg	300 Kg
Number of Shanks	1	2	3
Ripping Depth	40 cm – 60 cm	40 cm – 60 cm	40 cm – 60 cm
Under Frame Clearance	70 cm	70 cm	70 cm
Park Stand	Standard	Standard	Standard

We reserve the right to change any information on this brochure without prior notice.

ANIZ Tarim Endustri Ic ve Dis Ticaret Ltd.
Musallabaglari, Cakirli Caddesi 56
42110 Selcuklu
Konya, Turkey

Phone +90 (332) 236 0578
Fax +90 (332) 236 7905
<http://www.aniztarim.com.tr>
info@aniztarim.com.tr



MOUNTED SUBSOILER

ANIZ SUBSOILERS

Available Models:

SS12 Single Shank; SS20 Double Shank; SS30 Triple Shank.

ANIZ's heavy-duty 3-point subsoilers model SS12, SS20 and SS30 are perfect for fracturing hardpan compacted over years of use. Fits almost any type of agricultural tractors with a Category I or Category II 3-point hitch. Our subsoilers are capable of ripping the soil at 3-different positions of shank that aligning under frame clearance as 50 cm; 60 cm and 70 cm height by means of a fixing pin. This helps large tractors go deep and smaller tractors get more transport clearance. A Knob is attached to the lower back end of a shank by a piece of chain. It is used for drainage purposes to form a tubular space ensuring that excessive water is retained through. And shanks feature high carbon 30 mm steel, heat-treated replaceable tips.

Our subsoilers are built for years of trouble-free work with a minimum amount of maintenance.

If you interest please do not hesitate to contact to us: info@aniztarim.com.tr