

www.almontar.com



CATALOGUE



OVERVIEW

AL MONTAR Industrial has a competitive strategic position in the world of packaging materials through producing Poly strap, stretch wrap and self-adhesive tapes providing quality solution, optimum cost, and innovated solutions for Jordan, MENA region and globally.

AL MONTAR is implementing quality standards to make sure that all products are produced within the international standards to protect all packages from dust, rain, and ensure package security during handling, transportation and warehousing to achieve smooth operation, quality and low cost.

Contact Details:

AL MONTAR Industrial Trading EST

Al Hasan Industrial Area – Irbid, JORDAN

FACTORY: TEL: +962 2 2 7403310,

Sales: +962 79 6270012, email: sales@almontar.com

Management: +962 79 5885102, email: Hassan.saad@almontar.com

www.almontar.com

The systematic way of achieving success. Everything from a single source!



Milestones

AL MONTAR established in 2001 in Jordan as a specialized trading company for packaging materials.

AL MONTAR entered a new phase in July 2010 through the leadership of Mr. Hassan Saad to accelerate company growth, expansion and success.

AL MONTAR started up its own production for Stretch wrap in 2013.

AL MONTAR started of Polystrap - PP strap production line in 2016 with the latest technology at a capacity of 1000 tons per year and expanding.

AL MONTAR started production of self-adhesive tape, masking tapes, paper Kraft tape and other types of tapes in 2018.

AL MONTAR business operations are led by a competent team of managers, industrial engineers, technicians, operators and sales force.

AL MONTAR completed the requirements of ISO9001: 2015 certification in 2018 by SGS accreditation body.

AL MONTAR is always working to improve through continual improvement projects covering all process within the frame work of ISO 9001:2015 standards.

AL MONTAR is a well-known company of its high quality product and excellent timely service in order to exceed customer expectations.

AL MONTAR build up its objectives to provide service for domestic and export markets to accelerate its growth.

HISTORY



Vision

Our vision is to be the best packaging company in the Middle East through providing the best quality products, service, safety and optimum cost for our customers.

Mission

Our mission is to achieve excellence in terms of quality, innovation and service by offering eco-friendly products and a proactive consolidated presence in all local, regional and global markets.

Quality Policy

ALMONTAR is committed to exceed customer expectations in terms of high product quality, delivery time, distribution, promotional activities, best service and optimum costs. Deliver highest quality product at optimum cost by working with our suppliers as partners in order to achieve higher performance.

The top management is committed to this policy with full and effective implementation and it is also all employees' responsibility to fulfill with all requirements of this policy.

AL MONTAR established internal processes to ensure safe working environment and in compliance with legal and international health & safety requirement through safety change programs.

Environmental aspects are managed to cover internal impacts like noise reduction, waste management to ensure compliance with all applicable regulations.

AL MONTAR complies with all applicable governmental legal requirements and continually improve the effectiveness of our Quality management system ISO 9001:2015.

Ensure that all financial and human resources are in place through improving the level of training, promotes people to participate in process development taking into consideration health and safety for working environment

Customer's feedback plays a major role in our improvement projects through getting customer survey and full analysis is carried out in yearly basis.

ISO CERTIFICATE 9001:2015

ISO & EHS

Certificate CH18/1210

The management system of

Al Montar Industrial Trading Est.

Irbid - Al Hasan Industrial Area - Jordan

has been assessed and certified as meeting the requirements of

ISO 9001:2015

For the following activities

Manufacturing and distribution of Plastic Strap, Stretch Wrap and adhesive tapes.

Distribution of packaging machines and other packaging materials

This certificate is valid from 17 October 2018 until 16 October 2021
and remains valid subject to satisfactory surveillance audits
Recertification audit due before 12 October 2021
Issue 1. Certified since October 2018

Authorised by

S. Bani *Al Montar*

SGS Société Générale de Surveillance SA
Technoparkstrasse 1 8005 Zurich Switzerland
t +41 (0)44 445-16-80 f +41 (0)44 445-16-88 www.sgs.com

Page 1 of 1

SGS



This document is issued by the Company subject to its General Conditions of Certification Services accessible at www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues established therein. The authenticity of this document may be verified at <http://www.sgs.com/en/certified-clients-and-products/certified-client-directory>. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

PP Plastic strap


Polystrap is a universally applicable plastic strap for modern strap technology. Polystrap is produced in AL MONTAR facility in Jordan to achieve high quality strap with die range of application. Polystrap consists of the raw material Polypropylene (PP). By using a special process such as stretching to increase firmness and elasticity, the strap obtains further characteristics which ensure the user the advantages of a system.

Advantages

- Operation process designed to coordinate between strap quality, strapping technology, strap application and customer criteria
- High quality standard is ensured within the total quality management frame work, manufacturing experience and testing equipment.
- Comprehensive system to divide strap types with applications; hand tools, machines, automatic machines integrated in lines and systems.
- Short lead time, ability to react with urgent requests.
- Shock resistant due to its elasticity and ideal loads being transported.
- Outside storage; Polystrap does not corrode.
- Operational safety; no risks with sharp strap ends or recoiling.
- Operational comfort coils and rolls can be easily exchanged despite their considerable length.

Product list – PP

PRODUCT CODE	SIZE, mm		LENGTH	Breaking STRENGTH
	Width	Thickness	Mt.	N
PP0547A1W20	5	0.47	7000	500
PP0505A1W20	5	0.50	5500	550
PP0605A1W20	6	0.50	5500	650
PP0606A1W20	6	0.60	5000	800
PP0805A1W20	8	0.50	4000	950
PP0855A1W20	8	0.55	3500	1000
PP0806A1W20	8	0.60	2400	1050
PP0807A1W20	8	0.70	3000	1150
PP0955A1W20	9	0.55	3000	1100
PP0906A1W20	9	0.60	2400	1150
PP0907A1W20	9	0.70	2800	1250
PP1206A1W20	12	0.60	2000	1430
PP1207A1W20	12	0.70	1800	1450
PP1208A1W20	12	0.80	1700	1950
PP1506A1W20	15	0.60	1900	1850
PP1507A1W20	15	0.70	1500	2400
PP1508A1W20	15	0.80	1500	2700
PP1509A1W20	15	0.90	1100	3000
PP15.508A1W20	15.5	0.80	1300	3100



Colors: White or Black, all other colors are available upon request

Inner Core: 150, 200, 280, 400 mm.

Packing: 2 Rolls / Box.

Printable 1 – 2 colors



PET Plastic Strap

AL MONTAR offer the most ecological and economical strapping method at present for securing your cargo reliably. AL MONTAR already recognized the enormous advantages of PET straps over steel straps at a very early stage. PET strap embossed and smooth surfaces both are available.

Applications

AL MONTAR is supplying PET strap for manual, automatic and fully automatic high speed machines; vertical and horizontal types tested and approved. Width range from 9 mm to 16 mm. standard color is green, other colors can be produced upon request.

Advantages

PET Strap is widely used in many industries and main advantages are:

- High holding power
- High elongation of 11 – 22 %
- Tensile strength up to 550 N/mm²
- Stable at storage temperatures from 50°C to +70°C
- Best results when applied at temperature from +3°C/ +40°C
- Insensitive to ultraviolet radiation and water
- Shock absorbent
- Economical



Product List - PET

PRODUCT CODE	SIZE, mm		LENGTH	Breaking STRENGTH
	Width	Thickness		
PET9.506A1W40	9.5	0.60	3000	2000
PET9.506A1W40	9.5	0.70	2600	2400
PET1205A1W40	12.0	0.50	2500	2150
PET1206A1W40	12.0	0.60	2400	2600
PET1265A1W40	12.0	0.65	2500	2750
PET1207A1W40	12.0	0.70	2000	3000
PET1208A1W40	12.0	0.80	1600	3400
PET1209A1W40	12.0	0.90	1500	3850
PET12.57A1W40	12.5	0.70	2000	3100
PET1507A1W40	15.0	0.70	1500	3800
PET1508A1W40	15.0	0.80	1400	4300
PET1509A1W40	15.0	0.90	1085	4800
PET15.58A1W40	15.5	0.80	1330	4400
PET15.59A1W40	15.5	0.90	1200	4800
PET15.51A1W40	15.5	1.00	1000	5400
PET1908A1W40	19.0	0.80	1100	5400
PET1909A1W40	19.0	0.90	1000	6000
PET2510A1W40	25.0	1.00	800	6800
PET3210A1W40	32.0	1.00	700	8400

Stretch Wrap Material

AL MONTAR offers a large variety of stretch wrap films materials for different applications, manual, semi-automatic and fully automatic machines. Quality, Cost, service, reliability, performance, package securement are the characteristics of stretch film materials that we supply. Stretching ratio are designed from 150 % up to 400 %.

Stretch film is manufactured to protect and secure packages during the handling process, ensuring package protection from dust, rain and others.

Bio-degradable types are available upon request

PRODUCT

JR: Jumbo Rolls

AL MONTAR is supplying Jumbo Rolls, PE 7layer co-extruded, LLDPE (Cast technology), with a guaranteed pre-stretch of %150 – 250 %, it is used for converting to manual rolls and usually the gross weight is 50 – 60 kg, thickness range from 15 to 35 microns. Colors are clear, black and white.

HR: Hand Rolls

AL MONTAR is producing stretch film hand Rolls, PE 7layer co-extruded, LLDPE (Cast technology), with a guaranteed pre-stretch of %150 – 250 % for manual applications.

- Width: 400 - 500 mm.
- Thickness range: 15 – 35 microns
- Weight range: 2.0 – 3.0 kg per roll.
- Stretching ratio: 150 – 250 %.
- Length: 100 – 300 meters.
- Inner core: standard paper core, 38, 50 mm normal 52 mm or extended core.
- Packing: 4 or 6 rolls per carton.
- Color: clear, black and white.

MR = Machine Rolls

AL MONTAR is producing stretch film machine rolls, PE 7layer co-extruded, LLDPE (Cast technology), with a guaranteed pre-stretch of %180 – 400 % for automatic applications.

- Width: 500 mm.
- Thickness range: 15 – 35 microns.
- Weight range: 16.0 – 17.0 kg per roll.
- Stretching ratio: 180 – 400 %.
- Length: 1500 – 2500 meters according to specifications.
- Inner core: standard paper core 76mm.
- Packing: 50 rolls per pallet.
- Color: clear, black and white



TAPE SOLUTIONS FOR SECURE PACKAGING

AL MONTAR offers a large variety of Tapes to ensure that a product reaches its destination with full protection and total closing. Quality, Cost, service, reliability, performance, package securement are the characteristics of our Tapes that we produce.

Carton Sealing Tapes:

Our carton sealing solutions are used for securing shipments as well as reinforcing carton closures. Tapes comes with PP, PVC or Paper, all are suitable for manual or automatic applications.

TAPE Dispenser:

In order to make the packaging easy and fast, tape dispensers are widely used. We supply tape dispensers suitable for all types, 50 or 75 mm width user friendly for manual applications.

BOPP TAPE

BOPP Tapes with excellent sealing properties, adhesion and holding power

- Strong sealing properties
- Strong tensile strength
- Suitable Elongation
- Suitable for manual and machine application

Applications:

- Carton sealing
- General packaging

Specifications

Item	Code	ST45	ST43	ST40	ST38	ST37
Size	Total thickness (µc)	45	43	40	38	37
	Film Thickness (µc)	25	25	25	23	23
	Glue Thickness (µc)	20	18	15	15	14
	Adhesion to steel, kg/25mm	>0.60	>0.55	>0.50	>0.45	>0.45
	Holding power, 24 hr	>24 hr	>24 hr	>24 hr	>24 hr	>24 hr
	Tensile Strength,	>N/10 mm	>N/10 mm	>N/10 mm	>N/10 mm	>N/10 mm
Width	1, 1.5, 2, 3 Inches					
Length	60, 80,100, 160, 500 Yards (can be customized)					
Color:	Clear, white, brown, red, any other color					



PAPER KRAFT TAPE

Paper self-adhesive paper tapes with excellent sealing properties, high adhesion and holding power

- Strong sealing properties
- Strong tensile strength
- Best solution for heavy cartons
- High resistance for high temperature environment
- Excellent appearance

Applications:

- Carton sealing
- General packaging

Specifications

Item	Code	ST140	ST145	ST150	ST160	ST170
Size	Total thickness (µc)	140	145	150	160	170
	Initial force	>12	>14	>16	>18	>20
	Peel Strength, kg/m	>47	>48	>49	>50	>51
	Tensile Strength, kg/m	>3.3	>3.4	>3.5	>3.6	>3.7
	Temperature resistance, C	60	60	60	60	100
Width	1, 1.5, 2, 3 Inches					
Length	30 - 100 Yards (can be customized)					
Color:	Brown, white paper					

PRINTED SELF-ADHESIVE TAPES

Printed Self-Adhesive Tapes are produced in AL MONTAR facility in Jordan, we operate Flexographic state of the art technology using European machine T4 from flexo technique machinery up to 4 colors. Customers can have printing on tape for branding, product image, security reasons and company or product presentation on cartons.

We offer a wide range of printed self-adhesive tapes with a clear film color base, white or any base color, then printing image or logo up to 4 colors. Width range from ½, 1, 1.5, 2, 2.5, 3 inches. Total tape thickness range from 40 up to 50 microns



H-83 Strap Dispenser

- For PP plastic strapping
- Strap core I.D. 200, 280 mm
- 2 pcs / carton



H-84E Strap Dispenser

- For PP plastic strapping
- Strap core I.D. 200, 280 mm
- Economy model
- 2 pcs / carton



H-84 Strap Dispenser

- For both PET/PP plastic and oscillated wound steel strapping
- Robust design for heavy duty use
- Strap core I.D. 406 mm
- Face 75 mm or 150 mm
- 1 pc / carton



Packaging Machinery:

AL MONTAR is the agent for CYKLOP Germany in the MENA region, this offers the opportunity for customers to supply machines and materials from one source and ensure the smooth effective process.

Machinery are divided into:

- Strapping
- Wrapping
- Taping
- Coding

1- STRAPPING MACHINES:

Strapping Hand Tools:

Strapping Tools for PP Strapping

H-21 Tensioner

Strap width: 12 mm-19 mm
• 20 pcs / carton



Strapping Tools for PET and Heavy Duty PP

H-23 Tensioner

Strap width: 12 mm-19 mm
• 20 pcs / carton



Strapping Tools for Cord Strapping

H-22 Tensioner

Strap width: 9 mm-19 mm
• 20 pcs / carton



H-34 Sealer

Triple friction grip
Handle length 460 mm
• Strap width: 12 mm, 16 mm, 19 mm
• 10 pcs / carton



H-36 Sealer

Offset grip
For use with serrated seals
Handle length 460 mm
• Strap width: 12 mm, 16 mm
• 10 pcs / carton



H-25 Tensioner

Medium duty range
• Strap width: 9 mm-25 mm
• 10 pcs / carton



H-42 Combination Tool

Using cogwheel to drive windlass guarantees high tension and save effort
• Strap width: 12 mm, 16 mm
• 6 pcs / carton



H-36 Sealer

Offset grip
For use with serrated seals
Handle length 390 mm
• Strap width: 12 mm, 16 mm
• 10 pcs / carton



H-26 Tensioner

Heavy duty range
Machining made of alloy steel
• Strap width: 25 mm-40 mm
• 6 pcs / carton



Automatic strapping hand tools with battery: CLT 130 / CMT 260 / CHT 450

Automatic strapping hand tools with battery: CLT 130 / CMT 260 / CHT 450 Features:

- Full touch user interfaced for easier adjustment and user friendly for operators
- Variable tension speed controlled
- Strap alignment indication

Technical data sheet

Model	CLT 130	CMT 260	CHT 450
Operation mode	auto / semi / manual	auto / semi / manual	auto / semi / manual
Tension force range standard	400–1200 N	900–2500 N	1300–4500 N
Tension force range soft	150–750 N	400–1360 N	400–1600 N
Variable tension speed range	0–290 mm/s	0–220 mm/s	0–120 mm/s
Weight (incl. battery)	3,6 kg	3,8 kg	4,3 kg
Dimension (L x W x H)	370 x 141x 135 mm	370 x 141x 135 mm	370 x 143x 135 mm
Working temperature	-10 °C to +40 °C	-10 °C to +40 °C	-10 °C to +40 °C
Relative humidity	Up to 90%	Up to 90%	Up to 90%
Battery / Charger	Battery / Charger	Battery / Charger	Battery / Charger
Charger type	Bosch	Bosch	Bosch
Battery charger voltage	100 or 110 or 230 V	100 or 110 or 230 V	100 or 110 or 230 V
Charging time	15–30 min	15–30 min	25–35 min
Battery type	Bosch Li-Ion 18 V, 2,0 Ah	Bosch Li-Ion 18 V, 2,0 Ah	Bosch Li-Ion 18 V, 4,0 Ah
Cycles per battery charge			
• Low tension	800	800	800
• Medium tension	600	400	500
• High tension	400	200	300
Strap	Strap	Strap	Strap
Strap	PET / PP	PET / PP	PET / PP
Width	9–10, 12–13 mm	12–13, 15–16 mm	15–16, 18–19 mm
Thickness	PET 0,4–0,8 mm	0,5 - 1,0 mm	0,8–1,3 mm
	PP 0,5–0,8 mm	0,5 - 1,0 mm	0,5 - 1,0 mm
Advantages	Advantages	Advantages	Advantages
Real time indication of applied tension force	•	•	•
Variable tension speed	•	•	•
Favorite strapping function	•	•	•
Display color indication for tool status information	•	•	•
Strap alignment indication	•	•	•
Strap dust blow out vent	•	•	•
Battery protection	•	•	•
0–Tension welding	•	•	•

Pneumatic hand tool CP 500

Pneumatic strapping tool for heavy loads

Anywhere, where heavy packages make high tension necessary and where strapping is to be carried out in different areas, the CP 500 is the optimal choice. The pneumatic high-performance hand-tool is relatively light and easy to operate.

Features		DATA	
Accessories	Universal hanger for easier process	Strapping	PP / PET
	Steel plate as protection of the base area	Strap width	12 - 25 mm
Characteristics	Pneumatic strapping hand tool	Strap thickness	0.7 - 1.4 mm
	Adjustable to various strap widths	Tension:	up to 5,000 N
	Tensionless seal possible	Weight:	5,6 kg
	Easy handling	Dimensions:	300 x 155 x 200 mm
	Very strong seal	Seal	Friction seal
	Maintenance-friendly	Air pressure:	6 bar

Strapping Machines:

Semi-Automatic Strapping Machine M-Pac V

The M-Pac V is the latest semi-automatic strapping machine from Cyklop. The M-Pac V is used for strapping various packages with PP strap. The M-Pac V has a direct drive with fewer moving parts and therefore lower maintenance costs. The M-Pac V is a silent strapping machine (57 dB) and therefore also suitable for use in an office environment.

DATA	
Strapping	PP
Strap width	5 - 16 mm
Heating-up time	30 - 45 sec.
Tension	up to 450 N
Seal	Heat seal
Power supply	230 V, 1 Ph, 50 Hz, 0.35 KW

Automatic Strapping Machine (many models)

Automatic Strapping machines suitable for many industries, frame size, width: from 400 up to 1650 mm, height from 400 up to 850 mm. depending on the application the machine model is defined. Details information are available upon request. Machine speed, from 29 to 65 cycle per min.

2 Year Warranty

DATA	
Strapping	PP
Strap width	5 - 15 mm
Heating-up time	30 - 45 sec.
Tension	up to 450 N
Seal	Heat seal
Power supply	230 V, 1 Ph, 50 Hz, 0.35 KW



STRAPPING MACHINE: XZE

Fully automatic strapping press with vertical strapping The fully automatic and maintenance-friendly XZE series strapping press is fitted with the CFH-1 strapping head. These two combine to ensure fast strapping with maximum clamping force. The drive system delivers an exactly reproducible press force, accurate package height, adjustable press time and a defined interval pressure. The XZE ensures optimal securing of pallet loads in the corrugated cardboard, printing, paper and paper bag industries.



DATA

Strapping	PP/PET
Strap width	5 - 15 mm
Strap thickness	0.5 – 0.70 .
Load widths	600 – 2,100 mm
Load Height	max. 3,000
Tension	up to 5,500 N
Control	Siemens PLC S 7
Seal type	Friction Seal

Fully automatic vertical strapping machine XF/XP 111 M

The XF / XP 111 M is a fully automatic strapping machine with top sealer. Designed to strap large numbers of pallets of different sizes vertically with PP or PET band. This system is reliable, easy to use and installs the compact dimensions in confined spaces.



DATA

Strapping	PP/PET
Strap width	9 - 15 mm
Strap thickness	0.5 – 0.70 .
Load widths	600 – 2,100 mm
Load Height	max. 3,000
Tension	up to 5,500 N
Control	Siemens PLC S 7
Seal type	Friction Seal

Fully automatic vertical strapping machine XF/XP 112 M

The strapping machine XF / XP 112 M is a fully automatic strapping machine for vertically strapping large quantities of pallets of differing dimensions with PP or PET strap. The machine is equipped with a side sealer. This system is reliable, easy to use and can even be installed in limited spaces.



DATA

Strapping	PP/PET
Strap width	9 - 15 mm
Strap thickness	0.5 – 0.70 .
Load widths	600 – 2,100 mm
Load Height	max. 3,000
Tension	up to 5,500 N
Control	Siemens PLC S 7
Seal type	Friction Seal

AL MONTAR offers a very excellent selection of wrapping machines, reliable, effective, maintenance friendly, and price competitive;

Semi-Automatic Wrapping Machine – CST 201

Wrapping pallets with one press on the button

This stretch wrapper CST 201 is specially designed for handling pre-stretched wrapping film. The machine is easy to operate, with clear and simple button functions. Replacing the film roll is easy to do. There are access points in the base of the turntable to allow internal transport with a forklift.”

- Special program: Changing the film is simplified
- Mechanical brake
- Wrapping speed 12 rpm
- Able to save 6 wrapping programs
- Safe and easy application and cutting of film
- Extra function for adding corner protection

Semi-Automatic Wrapping Machine – CST 211

Reliable and cost-effective pallet wrapping

The stretch wrapper CST 211 is equipped with a simple electromagnetic brake pre-stretch system (maximum 150% pre-stretch). Film tension is manually regulated and adjusted. The machine is easy to operate, with clear and simple button functions. Replacing the film roll is easy to do. There are access points in the base of the turntable to allow internal transport with a forklift. Special program: Changing the film is simplified

- Infinitely variable speed turntable and film carriage
- Magnetic pre-stretch 150%
- Adjustable number of up and down windings
- Wrapping speed 12 rpm
- Possibility to save 6 wrapping programs
- Handles up to 15 pallets per hour



Fully Automatic Wrapping Machine: CSA 955

Fully automatic free arm stretch wrapper – up to 55 pallets / hour
The CSA 955 stretch wrapper can be integrated easily into an existing or new line. This film wrapper will ensure that the total costs of your production line are reduced. This results from the machine's high stretch percentage and maintenance-friendly nature. Driven by a heavy-duty turntable with external gearing

- Driven by a heavy-duty turntable with external gearing.
- Pre-stretch 150% – 200% – 250%
- Handles up to 55 pallets per hour
- Wrapping speed 25 rpm
- Simple replacement of film roll with rapid-load system



Fully Automatic Wrapping Machine: CSR 9120

Fully automatic ring stretch wrapper – up to 120 pallets / hour
The CSR 9120 pallet wrapper is a ring wrapping machine that is characterised by a unique external pre-stretch drive system. This robust machine can be easily integrated into a new or existing production line. The purchase of this film-wrapping machine will lead to cost savings due to its high pre-stretch percentage. The lifting frame is located on one side of the track which makes the machine extremely accessible. The patented drive system for the pre-stretch unit does not need sliding contacts. Driven by a heavy-duty turntable with external gearing.

- Flat-belt drive
- Without electronic components on the turning ring
- Flat-belt drive
- With motorized pre-stretch system (150 – 200 – 280% stretch)
- Handles up to 120 pallets per hour
- Compact design

TOPSHEET DISPENSER: CTFP

Fully automatic top sheet dispenser

The top-sheet dispenser CTFP is usually placed in a fully automatic packaging line in combination with a pallet wrapper to protect the load at the top against water, dust and other dirt. The machine is made of aluminum.

- Top sheet thickness 15-35 μ
- Top sheet 1300, 1600 or 1800 mm wide and up to 2000 mm length
- Handles up to 85 pallets per hour
- Required air pressure 6 Bar

TOPSHEET DISPENSER: TF / ITF

Fully automatic top sheet dispenser

The top-sheet dispenser TF/ITF is usually placed in a fully automatic packaging line in combination with a pallet wrapper to protect the load at the top against water, dust and other dirt. The machine is made of aluminum.

- Top sheet thickness 15-35 μ
- Top sheet 1200 x 1600 mm
- Handles up to 60 pallets per hour
- Required air pressure 6 Bar

STRETCH WRAPPER: CSM 211

Mobile stretch wrapper can be used anywhere

The stretch wrapper CSM 211 is a mobile stretch wrapper. The handle, with powered control buttons, allows easy transportation of the wrapper to the package. Replacing of the film roll is easy and fast with the (optional) flip-open stretch unit. Wrapping operation by simple touch controls. This modular machine is suitable for light and heavy use.

- Mobile stretch wrapper can be used anywhere
- Infinitely variable speed turntable up to 90 meters/min
- Infinitely variable speed film carriage
- Adjustable number of up and down windings
- Possibility to save 6 wrapping programs





CSM 211 / 212 / 212 Advance



CST 201



CST 211



CST 212



CST - TP Version



CST 212 Auto Advance



GL 205



GL 300



CST 915



CST 940



CST 940



CSA 211 / 212 advance



CSA 915



CSA 955 / 965



CSA 975



CSA twin



GL 2000 / GL 2000 twin



CSR 9120



CSR Twi

Cargill

Carlsberg

Chevron



Coca-Cola

CROWN CORK & SEAL

Heinz

DANONE



gsk
GlaxoSmithKline



★ **Heineken**

Henkel



L'ORÉAL

Lactis

LAFARGE



LUKOIL

Kimberly-Clark



Posteitaliane

NOVARTIS

**SAINT-GOBAIN
GLASS**



ROXANE



MERCADONA
SUPERMERCADOS DE CONSUMIDORES

Smurfit Kappa

Nestlé
Good Food, Good Life

coop

Electrolux



DB SCHENKER

ABB Power and productivity
for a better world™

REXEL
ELECTRICAL SUPPLIES



Contact details:

AL MONTAR Industrial Trading EST
Al Hasan Industrial Area – Irbid, JORDAN
FACTORY: TEL: +962 2 2 7403310

sales: +962 79 6270012
sales@almontar.com

sales: +962 795885102
Hassan.saad@almontar.com

www.almontar.com

CYKLOP
INTERNATIONAL

THE
STRAPPING
COMPANY

